



# HydroBoost

## ADVANCED PEROXIDE CLEANER ADDITIVE

HydroBoost is for use only with  
Fiberlock's Advanced Peroxide  
Cleaner (APC)

### Release the Power of APC

NET CONTENTS: 1 Quart

For Professional Use Only

HydroBoost is specifically designed to magnify the cleaning and stain removing power of Advanced Peroxide Cleaner (APC). Ideal for situations that demand extreme cleaning and powerful stain removal, HydroBoost works by instantly increasing the oxidation potential of Advanced Peroxide Cleaner.

When added to Advanced Peroxide Cleaner HydroBoost will further:

- Lift and Remove Deeply Embedded Dirt and Debris
- Remove Tough Stains caused by Mold and Mildew

Ideal for use on: Wood studs, trusses, beams and joists, plywood sheathing, OSB, engineered wood materials, grout, brick, stone and concrete surfaces.

#### DIRECTIONS FOR USE

USER MUST READ AND UNDERSTAND ALL INSTRUCTIONS AND PRECAUTIONS OUTLINED ON THIS LABEL AND THE CORRESPONDING SDS. FOR PROFESSIONAL USE ONLY.

ADDITIVE FOR USE WITH ADVANCED PEROXIDE CLEANER (#8314) ONLY. DO NOT MIX WITH ANY OTHER PRODUCT.

Note: The HydroBoost mixture should be used within 20-30 minutes to achieve the full effect of the product. Application to the substrate within 5-10 minutes is ideal. Plan your work accordingly so that you can apply all mixed product as quickly as possible. Do not return unused product to original container.

Add Hydroboost to Advanced Peroxide Cleaner at the following dilution ratio:

Maximum: 10:1 (12.8 oz./gallon) - 1 Quart of Hydroboost to 2.5 Gallons of APC

Maximum: 8:1 (16 oz./gallon) - 1 Quart of Hydroboost to 2 Gallons of APC

Mix contents thoroughly and apply within 30 minutes of mixing. Apply with a standard pump or hand trigger sprayer. Follow applications guidelines listed on the Advanced Peroxide Cleaner label for detailed application information.

**KEEP OUT OF REACH OF CHILDREN. FOR PROFESSIONAL USE ONLY.**

Store between 40°F (4.5°C) and 90°F (32°C)

24 hour Emergency call "CHEM-TEL" 1-800-255-3924

#### STORAGE

Store securely closed and upright in original container. Avoid shipping or storing below freezing or above 100°F. If product freezes, thaw at room temperature and shake gently to remix components. Store in locked area inaccessible to children.

**16 oz. - Empty to this line to make 1 gallon**

#### PRECAUTIONS

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F (32°C).

Always take care to avoid skin and eye contact by using protective measures such as nitrile rubber gloves (or equivalent) and safety glasses. Avoid breathing spray mists.

HydroBoost is a high pH additive formulated to boost the performance of the Advanced Peroxide Cleaner. Do not use this product on any surface that could be damaged by a high pH alkaline cleaner. Always test substrate in an inconspicuous area to determine if the solution will adversely affect the target material. This product is not intended for use on aluminum, magnesium, zinc, or other soft metals as pitting and etching can occur. Will degloss painted surfaces. Do not use on fire or finished woods as APC Booster can affect the finish of the wood. Do not use on glass. Protect floors and surrounding surfaces from contact. Promptly clean off any overspray or dripping from floors.

ADDITIVE FOR USE WITH FIBERLOCK'S ADVANCED PEROXIDE CLEANER ONLY. DO NOT MIX WITH ANY OTHER PRODUCT.

Do not take internally. Close container after each use. Keep from freezing. Properly dispose of all waste and unused product in accordance with Local, State and Federal regulations.

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the

suitability of this product, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet or Product Data Sheet available online at: [www.fiberlock.com](http://www.fiberlock.com).

HydroBoost and other marks on this label are trademarks of Fiberlock Technologies, Inc.

Contains: Water (7732-15-5), Sodium Metasilicate (6834-92-0), Surfactant Blend (N/A), Potassium Hydroxide (1310-58-3), Tetrasodium EDTA (64-02-8)

#### DANGER:



**Hazard Statements:**  
Causes serious eye damage.  
Causes severe skin burns and eye damage.  
Harmful if swallowed.  
Harmful if inhaled.

#### Precautionary Statements:

**Prevention:** Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe fumes, mist, vapors or spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product.

**Response IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **IF SWALLOWED:** Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician. **IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with water (or shower). Wash contaminated clothing before reuse. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

**Storage:** Store locked up.

**Disposal:** Dispose of contents/container in accordance with all local, state, and federal regulations.

Emergency Tel. No.: CHEM-TEL (U.S.): 1-800-255-3924  
(Outside the U.S.): 813-248-0585

## 8313-Q



8313-Q

6 11131 96404 0

ICP  
CONSTRUCTION  
150 Dascomb Rd.  
Andover, MA 01810  
(800) 342-3755  
[www.fiberlock.com](http://www.fiberlock.com)