

Scan this QR code with your smartphone for:

- Product Data Sheet and SDS
- Non-English Product Information
- Additional Product Information



Fiberlock
TECHNOLOGIES

Professional Products
Professional Results

CAUTION!
KEEP OUT OF REACH OF CHILDREN.
Do not take internally. Close container after each use.
Keep from freezing.
Store between 40°F (4.5°C) and 90°F (32°C)
24 hour Emergency "CHEM-TEL" - 1-800-255-3924

CAS. No.:
7732-18-5
107-21-1
13463-67-7
1317-65-3
Not Available*
*Contents partially unknown

CHEMICAL INGREDIENTS:
Water
Ethylene glycol
Titanium dioxide
Calcium carbonate
Latex resin solids

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Calculated VOC: 77 g/l

WARNING:



Hazard Statements:
Harmful if inhaled.
Causes mild skin irritation.
Causes serious eye irritation.

Precautionary Statements:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection (eye protection, gloves) during application. When grinding/sanding dry films, wear respiratory protection.

Response: If on skin, wash with plenty of soap and water. If in eyes, rinse cautiously for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If inhaled, remove victim to fresh air. If exposed or concerned, get medical advice.

Storage: Keep closures tight and containers upright to prevent leakage. KEEP FROM FREEZING. Product is non-combustible.

Disposal: The coating and any contaminated diking material should be thoroughly air dried and collected into drums. The drums should be sealed and labeled and land-filled or incinerated according to local, regional and national regulations.

Emergency Tel. No.: CHEM TEL: (U.S.): 1-800-255-3924 (Outside the U.S.): 813-248-0585

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of IAQ 3000, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at www.fiberlock.com.

IAQ, the IAQ Logo and other marks on this label are trademarks of ICP Construction, Inc.

8330-5
White



150 Dascomb Rd.
Andover, MA 01810
(800) 342-3755
www.fiberlock.com

PRODUCT APPLICATION

IAQ 3000 is supplied ready to use, but can be thinned sparingly with water for proper application consistency if necessary. IAQ 3000 should be applied full body, vertically and cross-hatched horizontally to remove all roller ridges and unevenness in the block filler. Brushing should be done with a short stubby brush, working the material well into any pinholes, pores and voids. Material should be applied in horizontal sections with block mortar lines serving as a guide. Spray application is not recommended because the silica content is abrasive to spray equipment.

COVERAGE

200 ft²/gal. - average (varies with porosity of block)

DRYING TIME @ 70°F 50% R.H

To Touch: 4-8 hours
Recoat : 24 hours

CLEANUP

Clean tools and drippings with warm soapy water before IAQ 3000 dries. Dispose of waste according to all existing local, state and federal regulations.

PRECAUTIONS

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F (32°C). Stir thoroughly. Do not mix with any other coatings, solvents or colors in oil. Do not apply IAQ 3000 when air or surface temperature is below 50°F or when drying conditions are poor. Keep from freezing. IAQ 3000 will reduce seepage, but is not intended for use as a waterproofer. For waterproofing applications do not use IAQ 3000, use IAQ 9000 Mold-Resistant Waterproofer. IAQ 3000 should not be used as a finish coat or be allowed to weather for more than 60 days without being finish coated. When applying with a sprayer, wear a NIOSH approved respirator with any R, P, N or HE filter. Use adequate ventilation during application. This coating is not intended for use as a mold-resistant coating.

IAQ

3000
Masonry Block Filler

- Fills pores and small voids
- Eliminates pin holing

- Easy to apply, alkali resistant formula
- Not water sensitive after application

NET CONTENTS: 5 Gallons

For Professional Use Only

Surfaces to be coated must be free of dust, mildew, mold, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap, efflorescence and other surface contamination. Nibs and mortar joints should be "bricked down" to remove all protrusions and mortar splatters. Clean mold stained surfaces with IAQ Advanced Peroxide Cleaner, or use an EPA registered antimicrobial disinfectant cleaner such as IAQ 2000, IAQ 2500, ShockWave or ShockWave RTU.

APPLICATION TOOLS

Apply IAQ 3000 with brush or roller. Spray application is not recommended because the mineral content is abrasive to spray equipment.

Brush: Synthetic, nylon or polyester bristle
Roller: Synthetic fiber 3/8" nap or longer