

Scan this QR code with your smartphone for:



- Product Data Sheet and SDS
- Non-English Product Information
- Additional Product Information

Fiberlock

TECHNOLOGIES

Professional Products
Professional Results



LEAD BARRIER COMPOUND

Professional Lead Encapsulant Type III (Interior/Exterior)

- For use in all 50 states
- Permanent lead abatement solution
- Class A fire rated
- Contains a bitter tasting anti-ingestant

NET CONTENTS: 5 Gallons

For Professional Use Only

Lead Abatement Products

WARRANTY:

Fiberlock Technologies warrants LBC for a maximum of twenty (20) years from the date the product is applied to form an effective barrier from the hazards of the encapsulated lead-based paint as prescribed in Fiberlock's latest product literature. The warranty described in this paragraph, expressed or implied, is including but not limited to the implied warranties of the salability and fitness for a particular purpose. User shall determine the suitability of LBC's use and assume any and all risks and liabilities that may arise in connection with the application of LBC. This warranty is extended only to the purchaser of LBC and does not apply to any damages which are a direct result of improper surface preparation and/or application, including, but not limited to the failure:

1. To properly apply LBC to a sound surface, which has been cleaned of foreign matter and dry at the time of application.
2. To apply LBC during non-freezing temperatures appropriate for the product application.
3. To apply LBC in full accordance with Fiberlock Technologies written application instructions and guidelines.

This warranty does not extend to, nor shall Fiberlock Technologies be liable for any damage resulting from any abuse of the encapsulated surface by tenants or occupants, improper maintenance, water damage, or other conditions beyond Fiberlock Technologies' control. The sole and only liability under this warranty shall be, at Fiberlock Technologies' option, either to replace the product if proved defective or to refund the purchase price paid. The purchaser of this product must notify Fiberlock at 150 Dascomb Road, Andover, Massachusetts 01810 within 45 days to advise of any suspected manufacturing defects. This warranty gives the purchaser specific legal rights and possible additional rights which may vary from State to State.

IMPORTANT INFORMATION FOR MASSACHUSETTS RESIDENTS

The Commonwealth of Massachusetts permits encapsulation as a form of abatement on any interior surfaces. For exterior surfaces in Massachusetts, when seeking compliance with regulations for lead poisoning prevention and control in residential housing and child-occupied facilities, all painted surfaces must be certified by a licensed inspector as intact and compliant prior to using LBC. When used for nonresidential structures, or when not seeking compliance for exterior surfaces, Massachusetts does not require this inspection before encapsulation.



For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of LBC, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at www.fiberlock.com.

LBC, the LBC Logo and other marks on this label are trademarks of ICP Construction, Inc.

5801-5 White



150 Dascomb Rd.
Andover, MA 01810
(800) 342-3755
www.fiberlock.com

CAUTION!

KEEP OUT OF REACH OF CHILDREN.

Do not take internally. Close container after each use.

Keep from freezing.

Store between 40°F (4.5°C) and 90°F (32°C)

24 hour Emergency "CHEM-TEL" -1-800-255-3924

CAS. No.:

7732-18-5

13463-67-7

1317-65-3

Not available*

Not available*

*Contents partially unknown

CHEMICAL INGREDIENTS:

Water

Titanium dioxide

Calcium carbonate

Proprietary surfactant

Latex resin solids

Calculated VOC: 88 g/l

WARNING:



Hazard Statements:

Harmful if inhaled.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause cancer.

Precautionary Statements:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection (eye protection, gloves) during application. When grinding/sanding dry films, wear respiratory protection.

Response: If on skin, wash with plenty of soap and water. If in eyes, rinse cautiously for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If inhaled, remove victim to fresh air. If exposed or concerned, get medical advice.

Storage: Keep closures tight and containers upright to prevent leakage. KEEP FROM FREEZING. Product is non-combustible.

Disposal: The coating and any contaminated diking material should be thoroughly air dried and collected into drums. The drums should be sealed and labeled and land-filled or incinerated according to local, regional and national regulations.

Emergency Tel. No.: CHEM TEL: (U.S.): 1-800-255-3924 (Outside the U.S.): 813-248-0585

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

8N32 GENERAL PURPOSE COATING SURFACE BURNING CHARACTERISTICS

To be used with Fiberlock general purpose coatings in accordance with manufacturer's instructions to produce finished Classified systems. For respective UL Classifications, see the general purpose coating label.