

- Superior Smoke Odor Blocking
- Superior Stain Blocking
- Blocks Pet Odors

- Superior Application Characteristics
- Superior Recoat-Ability
- Easily Topcoated

Fiberlock
TECHNOLOGIES

Professional Products
Professional Results

DANGER!
KEEP OUT OF REACH OF CHILDREN.
Do not take internally. Close container after each use.
Keep from freezing.
24 hour Emergency "CHEM-TEL" - 1-800-255-3924

CAS. No.: 7732-18-5
12251-27-3
13463-67-7
1344-00-9
2071-20-7
112-34-5
Not available*
*Contents partially unknown

CHEMICAL INGREDIENTS:
Water
Nepheline
Titanium Dioxide
Sodium aluminosilicate
Bis(diphenylphosphino)methane
Diethylene glycol monobutyl ether
Latex resin solids

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Calculated VOC: 49 g/l

DANGER:



Hazard Statements:
Causes serious eye irritation.
May cause cancer.
Harmful to aquatic life with long lasting effects.

Precautionary Statements:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection (eye protection, gloves) during application. When grinding/sanding dry films, wear respiratory protection.

Response: If on skin, wash with plenty of soap and water. If in eyes, rinse cautiously for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If inhaled, remove victim to fresh air. If exposed or concerned, get medical advice.

Storage: Keep closures tight and containers upright to prevent leakage. KEEP FROM FREEZING. Product is non-combustible.

Disposal: The coating and any contaminated diking material should be thoroughly air dried and collected into drums. The drums should be sealed and labeled and land-filled or incinerated according to local, regional and national regulations.

Emergency Tel. No.: CHEM TEL: (U.S.): 1-800-255-3924 (Outside the U.S.): 813-248-0585

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of this product, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at www.fiberlock.com.

Fiberlock Technologies, the Logo and other marks on this label are trademarks of ICP Construction, Inc.

3092-5
White



150 Dascomb Rd.
Andover, MA 01810
(800) 342-3755
www.fiberlock.com

ULTRA RECON

SMOKE ODOR SEALER

Brush: Synthetic, nylon or polyester bristle
Roller: 3/8" Nap Synthetic Fiber
Spray Settings:
Pressure: 2000-3000 P.S.I.
Tips: .015 to .021 tips

PRODUCT APPLICATION

Apply ULTRA RECON Smoke Odor Sealer generously and uniformly by brush, airless spray or roller. Apply one coat of ULTRA RECON Smoke Odor Sealer and ensure that the finished surface is properly sealed. Two-coats may be required on some porous or heavily stained surfaces. Topcoat floor applications when foot traffic or heavy storage is expected. ULTRA RECON Smoke Odor Sealer is tintable up to 2 oz. of universal liquid colorant per gallon. Can be directly applied to wallboard, sheetrock, wood, masonry and concrete. Ferrous metals may require a DTM primer to prevent flash rusting. Topcoat with water or oil-based paints. Not for use in HVAC systems.

COVERAGE

Smooth Surfaces: 200-400 ft²/gal.
Porous Surfaces: 100-200 ft²/gal.

DRYING TIME @ 70°F 50% R.H

To Touch: 30 Min.
Recoat: 2 Hours
Topcoat: 2 Hours

CLEANUP

Clean tools and drippings with warm soapy water before ULTRA RECON Smoke Odor Sealer dries. Dispose of waste according to all existing local, state and federal regulations.

PRECAUTIONS

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F. (32°C). Stir thoroughly. Do not mix with any other coatings, additives, solvents or colors in oil. Do not apply when air or surface temperature is below 45°F, or when drying conditions are poor or when surfaces are above a 15% moisture level content. In areas with high humidity, apply when surface temperature is 45°F or higher. Use adequate ventilation during application. When applying with a sprayer, wear a NIOSH approved respirator with any R, P, N or HE filter.

SURFACE PREPARATION


Warning! If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

Prior to applying Fiberlock's ULTRA RECON Smoke Odor Sealer (Ultra SOS™) it is critical that the substrate be thoroughly cleaned. Smoke odor encapsulation is a final step that needs to be part of a comprehensive smoke/odor management protocol. This protocol should include the following steps: Odor Cleaning, Odor Neutralization and Odor Encapsulation.

Fiberlock recommends cleaning with RECON Heavy Duty Cleaner or Extreme Duty Cleaner, followed by the application of RECON Extreme Duty Odor Counteractant. After the substrate is clean, dry and sound, apply ULTRA RECON Smoke Odor Sealer to encapsulate any residual odors that remain.

APPLICATION TOOLS

Apply ULTRA RECON Smoke Odor Sealer with a brush, roller or airless spray equipment.



Universal Restoration Primer/Sealer

Permanently Encapsulates Smoke Odors On Structural, Finished and Decorative Surfaces



EASILY ACCEPTS TOPCOAT



PREMIUM STAIN BLOCKER



MOISTURE PERMEABLE FINISH

NET CONTENTS: 5 Gallons

For Professional Use Only

Disaster Restoration Products