

QUALITY



KNOWLEDGE



SCIENCE



**FIBERLOCK**  
TECHNOLOGIES

**RECON**  
DISASTER CLEAN UP AND RESTORATION



# Extreme Duty Odor Counteractant

- Maximum Strength Odor Counteractant
- Apply by Spraying or as a Cleaning Additive
- Heavy Duty for Fire, Smoke, and Water Damage Restoration

3041

[www.fiberlock.com](http://www.fiberlock.com)

**FIBERLOCK**  
TECHNOLOGIES  
800.342.3755 [www.fiberlock.com](http://www.fiberlock.com)

**RECON**  
DISASTER CLEAN UP AND RESTORATION

Extreme Duty Odor Counteractant

Extreme Duty Cleaner

Citrus Solvent Cleaner

Heavy Duty Cleaner

Multipurpose Cleaning Wipes

Hand Sanitizer Wipes



For MSDS sheets and additional  
product information, go to  
[www.fiberlock.com](http://www.fiberlock.com)



Recon Extreme Duty odor Counteractant is a highly concentrated liquid odor counteractant formulated specifically for the treatment of surfaces after fire, water or smoke damage. This product chemically neutralizes the source of malodors and imparts a pleasant, long-lasting fragrance. The powerful multi-purpose odor counteractant removes malodors caused by tobacco, smoke, urine, mildew, vomit, body waste, pets, garbage, fire-produced odors, food spills and cooking odors. Ideal for use in institutions, hospitals, apartments, sanitariums, restaurants, factories, schools, hotels, kitchens, restrooms, latrines, septic systems, dumpsters, paper mills, recreational vehicles or anywhere malodors are a problem. May also be used as a deodorant booster for carpet cleaners and general-purpose cleaners.

**DIRECTIONS:**

FOR HAND SPRAYING: Spray undiluted product with a fine mist into air, onto carpets, drapes or directly onto source of odor.  
FOR DAMP MOPPING: Dilute 2 ounces per gallon into mop bucket cleaning solution and mop onto surface.  
FOR LAUNDRY: Add 1-2 ounces of concentrate to rinse cycle or add with softener to dispenser.  
FOR CARPET USE: Add 1-2 ounces of concentrate to each gallon of diluted shampoo solution.  
FOR SMOKE AND GARBAGE ODORS: Spray all surfaces thoroughly with undiluted product.  
FOR HOLDING TANKS: Add directly to holding tank. Use approximately 2 to 3 ounces for every 10 gallons of holding tank capacity.

**CAUTION**

EYE IRRITANT. MAY CAUSE SKIN IRRITATION WITH PROLONGED CONTACT. Avoid contact with skin, eyes, and clothing. Avoid prolonged breathing of concentrated vapors. Avoid breathing of mists. Do not take internally. Harmful if swallowed. Keep out of the reach of children. For professional use only.

**FIRST AID**

EYE CONTACT: Flush with water for at least 15 minutes. If irritation persists, call a physician.  
SKIN CONTACT: Wash thoroughly with water. If irritation persists, call a physician.  
INGESTION: Immediately drink large quantities of water. Do not induce vomiting. Call Poison Control Center or physician immediately.  
INHALATION: Remove to fresh air. Seek medical attention if victim is not responsive.

This product meets the maximum content requirements for Volatile Organic Compounds (VOCs) as established by State and Federal regulations.

**CONTAINS**

Water (7732-18-5), Isopropyl Alcohol (67-63-0), Nonylphenol Ethoxylate (9016-45-9), Cationic Surfactant (68424-85-1), Propylene Glycol (57-55-6), Perfume Oil (N/A), Odor Counteractant (N/A)

**MADE IN THE USA**

Manufactured for:  
Fiberlock Technologies  
Andover, MA 01810  
800.342.3755



7023-3027

NET CONTENTS:  
1 Gallon  
(3.8 Liters)