



MOLD REMEDIATION PRODUCTS
PRODUCT REFERENCE GUIDE

EPA Registered Fungicidal Coatings
Mold Resistant Coatings
Waterproofers, Primers, & Sealers
HVAC Sealants & Coatings

EPA Registered Disinfectant/Sanitizer/Cleaner/Fungicides
Cleaners

Product Characteristics							VOC Information					LEED® Credit EQ 4.2*	
Product Number	Package Size	Finish	Tintable ¹	Spray Settings		Coverage (ft ² /gal) ²	VOC (g/L)	VOC Regulation					
				PSI	Tip Size			U.S. EPA®	OTC®	CARB®	LADCO/MRPO®		SCAQMD®

EPA Registered Fungicidal Coatings	Product	Product Description	Color	Product Characteristics							VOC Information					LEED® Credit EQ 4.2*	
	Product Number	Package Size	Finish	Tintable ¹	PSI	Tip Size	Coverage (ft ² /gal) ²	VOC (g/L)	U.S. EPA®	OTC®	CARB®	LADCO/MRPO®	SCAQMD®				
	AfterShock³	Fungicidal Coating	White	8390	5 gallon 1 gallon	Semi-Gloss	✓	2000-3000	.017-.021	250-400	173	✓	✓	✓	✓	✓	✓
<p>AfterShock is the first EPA-registered antimicrobial coating designed to kill residual mold and mildew remaining after pre-cleaning contaminated surfaces. AfterShock also inhibits the future growth and spread of mold and mildew on the cured film surface in residential and institutional buildings. This extremely durable, easy to apply, 100% acrylic sealant offers the ultimate in durability in combination with excellent fungicidal characteristics to address mold growth from water damage. AfterShock is recommended for use on interior wall surfaces such as plaster, wallboard, drywall, concrete, masonry block, wood, primed metal and galvanized metal. AfterShock is also recommended for use on interior wood framing, primed metal, concrete, and wallboard inside the wall cavity.</p>																	

Mold Resistant Coatings	Product	Product Description	Color	Product Characteristics							VOC Information					LEED® Credit EQ 4.2*	
	Product Number	Package Size	Finish	Tintable ¹	PSI	Tip Size	Coverage (ft ² /gal) ²	VOC (g/L)	U.S. EPA®	OTC®	CARB®	LADCO/MRPO®	SCAQMD®				
	IAQ 6000	Mold Resistant Coating	White	8360	5 gallon	Matte	✓	2000-3000	.015-.019	250-400	75	✓	✓	✓	✓	✓	✓
<p>IAQ 6000 is a white, tintable mold-resistant coating for professional use, that contains an EPA-registered, broad-spectrum fungicide to prevent mold growth on the surface of the cured film. IAQ 6000 is a durable, flexible, and permeable 100% acrylic water-based coating that can withstand the moist, humid conditions present in environments conducive to mold growth.</p>																	
	IAQ 6000 HD	Heavy Duty Mold Resistant Coating	White	8362	5 gallon	Matte	✓	2200-2800	.019-.025	250-400	91	✓	✓	✓	✓	✓	✓
<p>IAQ 6000HD is a white, tintable, high-build mold-resistant coating for both professional use in the remediation of mold and the prevention of mold growth during new building construction. This product contains an EPA-registered, broad-spectrum fungicide to prevent mold growth on the surface of the cured film.</p>																	
	IAQ 6100	Mold Resistant Coating	Clear	8361	Semi-Gloss	Non-Flat		2000-2800	.015-.019	350-600	90	✓	✓	✓	✓	✓	✓
<p>IAQ 6100 is a clear mold-resistant coating for professional use that contains an EPA-registered, broad-spectrum fungicide to prevent mold growth on the surface of the cured film. IAQ 6100 is a durable, flexible, and permeable 100% acrylic water-based coating that applies white so the user can ensure complete and thorough application, and then dries to a clear finish.</p>																	
	IAQ 6040	Mold Resistant Sealant	Violet	8363	5 gallon	N/A		1300-2000	.015-.021	400-450	89	✓	✓	✓	✓	✓	✓
<p>IAQ 6040 is a low-viscosity, translucent violet sealant designed to seal new construction materials and resist fungal growth. This specially formulated, water-based coating contains EPA-registered antimicrobials that inhibit the growth of mold on the surface of the cured stain.</p>																	
	IAQ 6500	Mold Resistant Coating	Black	8365	5 gallon	Eggshell		1500-3000	.015-.023	250-400	77	✓	✓	✓	✓	✓	✓
<p>IAQ 6500 is a black, mold-resistant coating for professional use that contains an EPA-registered, broad-spectrum fungicide to prevent mold growth on the surface of the cured film. IAQ 6500 is a durable, flexible, and permeable 100% acrylic water-based semi-gloss coating that can withstand the moist, humid conditions present in environments conducive to mold growth.</p>																	

Waterproofers, Primers, & Sealers	Product	Product Description	Color	Product Characteristics							VOC Information					LEED® Credit EQ 4.2*	
	Product Number	Package Size	Finish	Tintable ¹	PSI	Tip Size	Coverage (ft ² /gal) ²	VOC (g/L)	U.S. EPA®	OTC®	CARB®	LADCO/MRPO®	SCAQMD®				
	IAQ 3000	Masonry Block Filler	Off-White	8330	5 gallon	Non-Flat		2500-3000	.015-.019	100-200	81	✓	✓	✓	✓	✓	✓
<p>IAQ 3000 is a high quality interior and exterior block filler formulated to fill small imperfections and pinholes in masonry block and porous concrete before top coating. This 100% acrylic block filler is easy to apply, alkali resistant and provides a uniform surface capable of receiving all types of finish coats.</p>																	
	IAQ 4000	Acrylic Latex DTM Primer	White	8340	5 gallon	Non-Flat	✓	1500-2500	.015-.021	400-450	98	✓	✓	✓	✓	✓	✓
<p>IAQ 4000 is a rust inhibiting 100% acrylic latex metal coating for use on ferrous metal, galvanized metal and other surfaces exposed to general industrial and atmospheric conditions. IAQ 4000 has excellent water resistance and excellent resistance to most alkalis, detergents and mild acids. Ideal for metal studs. Use two coats for existing rust.</p>																	
	IAQ 5000	Stain Blocking Primer	White	8350	5 gallon	Non-Flat	✓	2200-2800	.015-.017	400-500	93	✓	✓	✓	✓	✓	✓
<p>IAQ 5000 is a quick drying, high performance 100% acrylic latex coating specifically designed to prime stained or water damaged surfaces. This stain blocking primer provides exceptional adhesion and stain blocking properties and may be used on interior or exterior surfaces to prevent most bleeding type stains, seal porous surfaces and provide adhesion to hard and glossy surfaces.</p>																	
	IAQ 9000	Mold Resistant Masonry Waterproofer	White	8395	5 gallon	Non-Flat	✓	Not Recommended		100-125	158	✓	✓	✓	✓	✓	✓
<p>IAQ 9000 is a mold-resistant, low-odor, waterproofing coating that is specially formulated to stop water from penetrating through a variety of interior and exterior surfaces including above or below grade masonry walls, cinder and concrete blocks, stucco, brick, retaining walls, basements, and foundations. IAQ 9000 resists up to 10 PSI of water pressure, twice the government standard.</p>																	

¹Applicable Fiberlock products are tintable up to 2oz per gallon. Contact Fiberlock for more information on tinting.

²Coverage based on application on smooth surface. Coverage may vary based on porosity of surface and application techniques.

*The Fiberlock Technologies products shown in the table below, comply with the credit requirements for the U.S. Green Building Council LEED® for New Construction & Major Renovations Version 2.2 Rating System for the Indoor Air Quality - EQ Credit 4.2: Low-Emitting Materials: Paints & Coatings. Products are not reviewed or certified under the LEED Rating System. LEED credit requirements cover the performance of materials in aggregate, not the performance of individual products or brands. For more information on LEED, visit www.usgbc.org/leed. For additional information visit www.fiveshadesofgreen.com.

³Contact Fiberlock regarding use in California.

IAQ
Mold Remediation Products

	Product	Product Description	Color	Product Characteristics						VOC Information					LEED® Credit EQ 4.2		
				Product Number	Finish	Package Size	Tintable ¹	Spray Settings ³		Coverage (ft ² /gal) ²	VOC (g/L)	VOC Regulation Group					
								PSI	Tip Size			U.S. EPA®	OTC®	CARB®		LADCO/MRPO®	SCAQMD®
HVAC Sealants & Coatings	IAQ 7000	HVAC Sealant	White	8370	Gloss	5 gallon	✓	2200-3000	.017-.023	100-200	52	✓	✓	✓	✓	✓	✓
	IAQ 7000 is a quick drying water-based adhesive coating for use on duct liner insulation surfaces. IAQ 7000 is designed to reinforce HVAC insulation materials. IAQ 7000 is manufactured from premium acrylic resins to allow for optimal durability and flexibility and can be used in residential, commercial, or industrial facilities requiring moisture and mold resistance.																
	IAQ 7500	HVAC Sealant	Clear	8375	Gloss	5 gallon		2200-3000	.017-.023	100-200	54	✓	✓	✓	✓	✓	✓
	IAQ 7500 is a quick drying water-based adhesive coating for use on duct liner insulation surfaces. IAQ 7500 is designed to reinforce HVAC insulation materials. IAQ 7500 is manufactured from premium acrylic resins to allow for optimal durability and flexibility and can be used in residential, commercial, or industrial facilities requiring moisture and mold resistance.																
	IAQ 8000	HVAC Sealant	White	8380	Semi-Gloss	5 gallon	✓	2500-3000	.019-.023	200-600	90	✓	✓	✓	✓	✓	✓
IAQ 8000 is a dual-purpose, high performance coating designed for use in ductwork. IAQ 8000 dries to form a durable, flexible, moisture-resistant protective coating. Its semi-gloss finish minimizes biofilms and dirt buildup on the coating surface that provides nutrients that feed mold colonies. IAQ 8000 is high in viscosity to provide maximum bridging ability on insulation materials.																	
IAQ 8500	HVAC Sealant	Black	8385	Semi-Gloss	5 gallon		2500-3000	.019-.023	200-600	89	✓	✓	✓	✓	✓	✓	
IAQ 8500 is a dual-purpose, high performance coating designed for use in ductwork. IAQ 8500 dries to form a durable, flexible, moisture-resistant protective coating. Its semi-gloss finish minimizes dirt buildup on the coating surface that provides nutrients that feed mold colonies. IAQ 8000 is high in viscosity to provide maximum bridging ability on insulation materials.																	

	Product	Product Description	Color	Product Number	Package Size	Active Ingredient	pH	Dilution ratio	
EPA Registered Disinfectant/Sanitizer/Cleaner/Fungicides	Shockwave	Disinfectant/Sanitizer/Cleaner/Fungicide	Clear Blue	8310	1 gallon 10 oz bottle	Quaternary Ammonium Chloride	11.7	2-4 oz. /gallon	
	ShockWave is an EPA-registered disinfectant, sanitizer and cleaner designed specifically for mold remediation contractors. ShockWave is designed to meet all your disinfecting, sanitizing, cleaning, and deodorizing needs. ShockWave is strong enough to be used as a hospital grade disinfectant, and has been specifically formulated to be used on both porous and non-porous materials. ShockWave is a powerful concentrated quaternary ammonium chloride blend that yields up to 64 gallons of usable product from every gallon of concentrate. ShockWave has been tested to kill 80+ organisms including Aspergillus niger, Penicillium spinulosum, E. coli, Salmonella, HIV, Hepatitis-B, Herpes, Poliovirus, and many other pathogenic and environmental microbial organisms.								
	Shockwave RTU	Disinfectant/Sanitizer/Cleaner/Fungicide	Clear	8316	5 gallon 1 gallon	Quaternary Ammonium Chloride	11.7	Ready-to-Use	
	ShockWaveRTU is an EPA-registered disinfectant, sanitizer and cleaner designed specifically for mold remediation contractors. Shock-WaveRTU is designed to meet all your disinfecting, sanitizing, cleaning, and deodorizing needs. ShockWaveRTU is strong enough to be used as a hospital grade disinfectant, and has been specifically formulated to be used on both porous and non-porous materials. ShockWaveRTU is a powerful ready-to-use quaternary ammonium chloride blend, which is ideal for use when clean water is not readily available or for any situation where a ready-to-use formula is required.								
	IAQ 2000	Disinfectant & Fungicide Concentrate	Blue	8320	1 gallon	Quaternary Ammonium Chloride	11.7	2 oz. / gallon	
IAQ 2000 is an EPA registered disinfectant and cleaner designed to kill and control fungal, bacterial, and virucidal growth. Fiberlock IAQ 2000 is a concentrated, phosphate free formulation designed to provide effective cleaning, deodorizing, and disinfection specifically for schools, retail business, and commercial buildings, and other places where housekeeping is of prime importance in controlling the hazard of microbial contamination. When used as directed, Fiberlock IAQ 2000 disinfects hard, nonporous, inanimate, environmental surfaces, including floors and walls, that are prone to problems caused by microorganisms.									
IAQ 2500	Disinfectant & Fungicide	Purple	8325	5 gallon	Quaternary Ammonium Chloride	11.7	Ready-to-Use		
IAQ 2500 is designed specifically as a general non-acid cleaner and disinfectant for use in homes, schools, office buildings, and retail businesses. It is formulated to disinfect hard, nonporous, inanimate environmental surfaces: floors, walls, glazed porcelain, glazed ceramic tile, plastic surfaces, bathrooms and cabinets. For plastic and painted surfaces; spot test on an inconspicuous area before use. A rinse with potable water is required for surfaces in direct contact with food.									

Cleaners	IAQ 1000	Mold & Mildew Stain Remover	Clear	8315	5 gallon	Hydrogen Peroxide	6.5 - 7.5	Ready-to-Use
	IAQ 1000 is a hydrogen peroxide based biodegradable, chlorine free cleaner. IAQ 1000 is pH-neutral, and contains an agent that will whiten and brighten while cleaning, but does not contain sodium hypochlorite (bleach). IAQ 1000 is suitable for use in water damage restoration situations to remove odor causing mold, mildew, bacteria, and other microbial growth on porous, semi-porous, and non-porous materials. IAQ 1000 contains no dyes or perfumes, and is not corrosive like many industrial cleaners. IAQ 1000 is specifically designed for cleaning after water damage, sewer backups and floods. IAQ 1000 is supplied in a powerful, ready-to-use formula that can be applied directly from the container. IAQ 1000 is shipped in a light block box to maximize life span.							

¹Applicable Fiberlock products are tintable up to 2oz per gallon. Contact Fiberlock for more information on tinting.

²Coverage based on application on smooth surface. Coverage may vary based on porosity of surface and application techniques.

^{*}The Fiberlock Technologies products shown in the table below, comply with the credit requirements for the U.S. Green Building Council LEED® for New Construction & Major Renovations Version 2.2 Rating System for the Indoor Air Quality - EQ Credit 4.2: Low-Emitting Materials: Paints & Coatings. Products are not reviewed or certified under the LEED Rating System. LEED credit requirements cover the performance of materials in aggregate, not the performance of individual products or brands. For more information on LEED, visit www.usgbc.org/leed. For additional information visit www.fiveshadesofgreen.com.

³For HVAC coating, consider robotic application. Visit www.lloydssystems.com for more information.



Fiberlock Technologies Inc.
150 Dascomb Rd.
Andover, MA 01810
800-342-3755
www.fiberlock.com

MOLD REMEDIATION PRODUCTS
COMPETITIVE PRODUCTS GUIDE

Mold Remediation Products

Fiberlock Lead Abatement Products

		AfterShock™	IAQ™ 6000	IAQ™ 6000HD	IAQ™ 6040	IAQ™ 6100	IAQ™ 6500	IAQ™ 7000	IAQ™ 7500	IAQ™ 8000	IAQ™ 8500	IAQ™ 9000
Company	Product											
Aegis®	Aegis Microbe Shield™			✓								
Alistagen®	CaliWel™		✓									
	CaliWel HVAC™								✓			
	CaliWel Industrial™			✓								
American Coatings®	MAR-T126™		✓									
Anabec®	NB-12™				✓							
	NewBuild 30™											
	X-70™					✓						
	X-70 Plus™	✓	✓									
Controlled Release Tech®	Bioflex™		✓									
EnviroCare™	EnviroShield ES-100™					✓						
Foster®	40-10™									✓		
	40-11™										✓	
	40-20™	✓	✓									
	40-23™							✓			✓	
	40-25™	✓										
	40-30™						✓					
	42-42™				✓							
	40-50™	✓	✓									
	40-51™					✓						
Global Encasement®	MoldDon't™	✓	✓									
Porter®	Portersept®		✓									
	Portersept® HVAC									✓		
Sentinel®	24-7™	✓	✓									
Siamons®	Concrobium®					✓						
Unsmoke®	Surface Shield™					✓			✓			
	Unsoot™								✓			
	Unsoot™ 2								✓			
Valprene®	VI 220™									✓		
	VI-230™										✓	
	VI 250™			✓								
	VI 251™				✓							
Zinsser®	Perma-Guard™					✓						
	PermaWhite®	✓	✓									
	Watertite™											✓

Comparable Products

		Fiberlock Lead Abatement Products				
Company	Product	ShockWave™	ShockWave™ RTU	IAQ™ 2000	IAQ™ 2500	IAQ™ 1000
3M®	HB Quat™			✓		
American Coatings®	MAR-T54™				✓	
Anabec™	Advanced Cleaning Solution™					✓
	Anashield™					✓
BBJ®	Disinfectant Cleaner™		✓			
Benefect®	Broad Spectrum Disinfectant™	✓	✓	✓	✓	
Biocide™	Oxine®	✓				
Bio-Cide™	EnviroCON™				✓	
Caltex International®	Calbrite™					✓
Contec®	Sporicidin® Disinfectant Spray™	✓	✓	✓	✓	
DuPont®	Cryocide®				✓	
	RelyOn™	✓				
	Virkon®	✓				
Envirocare™	Moldex®		✓			
Foster®	40-80™				✓	
Global Encasement®	DeMold™				✓	
	PremeClean™					✓
Metrex®	Cavicide®			✓		
Modec®	MDF-500™		✓			
Pure Bioscience®	PureGreen24™	✓	✓			
Safe Encasement®	SE-IC Cleaner™					✓
Sentinel®	825 Mold/Mildew Stain Remover™					✓
Trask®	Impact™			✓		
Theochem®	Moldstat Plus™	✓				
	PeroxyCling™					✓
Unsmoke®	Disinfectant SprayPlus™	✓	✓	✓	✓	
	Microban™	✓	✓	✓	✓	
Valprene®	VI 400™	✓				
Zinsser®	Jomax Mold/Mildew Stain Remover™					✓
	Perma-Wash™				✓	

Disclaimer: Every attempt has been made to ensure the information presented in this page is accurate, Fiberlock can take no responsibility for commercial decisions made based on the information presented. Please consult the original references provided. If you believe information about a product is inaccurate or misrepresentative, please contact us and we will rectify any errors immediately. The names of actual companies and products mentioned herein may be the trademarks of their respective owners.

Fiberlock Technologies Inc.
150 Dascomb Road
Andover, MA 01810
800-342-3755
www.fiberlock.com