

Product	Application Method	Active Ingredient	Dilution	Color	Unit Size
<b>Broad Spectrum Cleaner</b>					
IAQ 1000	Pump, Trigger Sprayer	Hydrogen Peroxide	Premixed	Clear	5 gallon
IAQ 1000 is a hydrogen peroxide based biodegradable, chlorine free cleaner. IAQ 1000 is pH-neutral, and will whiten and brighten while cleaning, but does not contain sodium hypochlorite (bleach).					

**Disinfectants and Sanitizers**

ShockWave	Pump, Trigger Sprayer	Quaternary Ammonium Chlorides	2-4 oz/gal	Clear Blue	10 oz, 1 gallon
ShockWave is a concentrated, EPA-registered, quaternary ammonium chloride cleaner, that disinfects hard, nonporous surfaces, and also sanitizes porous and semi-porous surfaces subject to microbial contamination. ShockWave is available in 1-gallon jugs and convenient 10-ounce bottles, the proper amount for five gallons of usable product.					
ShockWaveRTU	Pump, Trigger Sprayer	Quaternary Ammonium Chlorides	Premixed	Clear Blue	1, 5 gallon
ShockWave RTU is a ready-to-use, EPA-registered, quaternary ammonium chloride cleaner, that disinfects hard, nonporous surfaces, and also sanitizes porous and semi-porous surfaces subject to microbial contamination.					
IAQ 2000	Pump, Trigger Sprayer	Quaternary Ammonium Chlorides	2-4 oz/gal	Clear Blue	1 gallon
Fiberlock IAQ 2000 is an EPA registered phosphate-free, quaternary ammonium chloride formulation designed for use in a diverse assortment of buildings, both residential and commercial. Fiberlock IAQ 2000 is a concentrated formula that will disinfect hard, nonporous inanimate environmental surfaces.					
IAQ 2500	Pump, Trigger Sprayer	Quaternary Ammonium Chlorides	Premixed	Clear Blue	5 gallon
EPA registered to disinfectant hard, non-porous, inanimate environmental surfaces. Fiberlock IAQ 2500 is a pre-mixed, ready to use formula that can be applied straight from the container.					

Product	Coverage (Sq. ft./gallon)	Application Method	Active Ingredient	Color	Unit Size
---------	---------------------------	--------------------	-------------------	-------	-----------

**Fungicidal Coating**

AfterShock	175-350	Brush, Roll, Spray	Chlorothalonil	White	1, 5 gallon
AfterShock is the first coating EPA-registered to kill residual mold and mildew remaining after pre-cleaning contaminated surfaces. AfterShock also inhibits the growth and spread of mold and mildew on the cured film surface in residential and institutional buildings.					

**Mold Resistant Coatings**

IAQ 6000	250-400	Brush, Roll, Spray	Fungitrol	White (tintable)	5 gallon
Fiberlock IAQ 6000 is an extremely durable coating developed to withstand moist, humid conditions that provide the ideal environment for fungal growth. Fiberlock IAQ 6000 contains an EPA-registered, broad-spectrum fungicide to prevent the growth of mold on the surface of the cured film.					
IAQ 6100	350-600	Brush, Roll, Spray	Fungitrol	Clear	5 gallon
Clear version of IAQ 6000. Its clear finish allows for post-remediation visual inspection of treated surfaces. IAQ 6100 applies white for easy application then dries to a clear finish.					
IAQ 6500	250-400	Brush, Roll, Spray	Fungitrol	Black	5 gallon
IAQ 6500 is a black version of IAQ 6000 to be used in areas where a white finish may be undesirable, such as attics, crawl spaces, etc.					

**Mold Resistant Coatings for New Construction**

IAQ 6000HD	250-400	Brush, Roll, Spray	Fungitrol	White (tintable)	5 gallon
Fiberlock IAQ 6000HD is a high-build, mold-resistant coating designed to help prevent mold growth from occurring in new building construction. Fiberlock IAQ 6000HD is designed for use on building materials including gypsum wallboard, oriented strand board (OSB), wood framing timbers, plywood, and any other surface where a flexible high-build mold-resistant coating is necessary.					
IAQ 6040	400-450	Brush, Roll, Spray	Fungitrol	Violet	5 gallon
Fiberlock IAQ 6040 is a low viscosity, translucent violet sealant designed to seal new construction materials and resist fungal growth. The low viscosity 100% acrylic formula is easy to apply, and the translucent finish will not block the appearance of treated building materials.					

\*Coverage based on application on smooth surface. Coverage may vary based on porosity of surface and application techniques.

Product	Coverage (Sq. ft./gallon)*	Application Method	Active Ingredient	Color	Unit Size
<b>IAQ 7000</b>	100-200	Brush, Roll, Spray	Fungitrol	White (tintable)	5 gallon
Fiberlock IAQ 7000 is a quick drying water-based adhesive coating/encapsulant for use on duct liner insulation surfaces. Fiberlock IAQ 7000 dries to form a durable, flexible, moisture-resistant protective coating on the duct liner insulation material. Its semi-gloss finish minimizes dirt buildup on the coating surface which can provide nutrients that feed mold growth.					
<b>IAQ 7500</b>	100-200	Brush, Roll, Spray	Fungitrol	Clear	5 gallon
IAQ 7500 is a clear version of IAQ 7000. IAQ 7500 applies white for easy application then dries to a clear finish.					
<b>IAQ 8000</b>	600 <sup>1</sup>	Brush, Roll, Spray	Fungitrol	White (tintable)	5 gallon
Fiberlock IAQ 8000 is designed to penetrate and reinforce duct liner or duct board insulation materials. Fiberlock IAQ 8000 can also be used to seal unlined duct work prior to component removal, preventing microbial particulate from becoming airborne.					
<b>IAQ 8500</b>	600 <sup>1</sup>	Brush, Roll, Spray	Fungitrol	Black	5 gallon
IAQ 8500 is a black version of IAQ 8000.					

### Preparation Products

<b>IAQ 3000</b>	200	Brush, Roll, Spray	N/A	White (tintable)	5 gallon
Fiberlock IAQ 3000 is a high quality interior and exterior block filler formulated to fill small imperfections and pinholes in masonry block and porous concrete before topcoating. This product contains mineral type fillers and fine silica aggregates which fill voids in masonry surfaces.					
<b>IAQ 4000</b>	400-450	Brush, Roll, Spray	N/A	White (tintable)	5 gallon
Fiberlock IAQ 4000 is a rust inhibiting 100% acrylic latex metal coating for use on ferrous metal, galvanized metal and other surfaces exposed to general industrial and atmospheric conditions. Fiberlock IAQ 4000 has excellent water resistance and excellent resistance to most alkalis, detergents and mild acids. Does not contain flammable solvents, and has low odor and fast recoatability.					
<b>IAQ 5000</b>	400-500	Brush, Roll, Spray	Microban	White (tintable)	5 gallon
Fiberlock IAQ 5000 is a quick drying, high performance 100% acrylic latex coating specifically designed to prime stained or water damaged surfaces. This stain blocking primer provides exceptional adhesion and may be used on interior or exterior surfaces to seal porous surfaces, provide adhesion to hard and glossy surfaces, and prevent most bleeding type stains.					

### Mold Resistant Waterproofer

<b>IAQ 9000</b>	100	Brush, Roll, Spray	Fungitrol	White (tintable)	5 gallon
Fiberlock IAQ 9000 is a low-odor mold resistant waterproofing coating. It is designed to stop 10 psi of water pressure water from penetrating through a variety of interior and exterior surfaces including above or below grade masonry walls, cinder and concrete block, stucco, brick, retaining walls, and foundations.					

\*Coverage based on application on smooth surface. Coverage may vary based on porosity of surface and application techniques.

1. Coverage for IAQ 8000/8500 based on application of unlined duct. Porous insulation will yield a coverage rate of 75-175 Sq. ft./gallon.