

IAQ 6000™

Mold-Resistant Coating

DESCRIPTION

Product No.: 8360 White

Fiberlock IAQ 6000 is an extremely durable coating developed to withstand moist, humid conditions that provide the ideal environment for fungal growth. This easy to apply, 100% acrylic coating offers the ultimate in durability in combination with excellent mold resistance. Fiberlock IAQ 6000 contains an EPA-registered, broad-spectrum fungicide to prevent the growth of mold on the surface of the cured film. Plus, its smooth finish minimizes dirt buildup that provides nutrients for mold growth. Fiberlock IAQ 6000 is highly recommended for use on hard, non-porous surfaces such as concrete, masonry block and metal, and may be used as a mold-resistant paint system on plaster, wallboard, sheetrock, and wood surfaces. Fiberlock IAQ 6000 does not contain any compounds such as barium, boron or zinc, which are present in other mold-resistant coatings.

SURFACE PREPARATION

Surfaces to be coated must be free of dust, mildew, mold, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap and other surface contamination. (Clean mold-contaminated surfaces with IAQ 1000, or an EPA-registered Anti-Microbial Disinfectant Cleaner such as Fiberlock IAQ 2000 Fiberlock IAQ 2500 or Shockwave, to kill microbial contamination.) Patch any irregularities with an appropriate patching compound. Fiberlock IAQ 6000 is self-priming over bare sheetrock, composition board, ceiling tile and concrete.

Wallboard, Sheetrock, Gypsum Board - Joint cement should be sanded smooth, but avoid abrading the paper.

Ferrous Metal - Clean, then prime with Fiberlock IAQ 4000™ acrylic DTM primer.

Wood - Seal knots and stains with Fiberlock IAQ 5000™ stain-blocking primer.

Masonry Block - Apply one coat of Fiberlock IAQ 3000™ acrylic block filler if a denser surface is desired.

PROPERTIES

- Percent Solids: 42.1% by weight
33.0% by volume
- Viscosity at 70°F: 102 ± 5 Krebs Units
- Weight per gallon @ 70°F: 9.7 lbs
- Flash Point: Noncombustible
- Odor: Virtually odorless
- Shelf Life: @ 70°F, 36 months minimum
(in original factory sealed containers)
- Finish: 45° ± 5° 60° Architectural Matte
- Coverage:
 - Smooth surfaces: 250-400 ft²/gal
 - Porous Surfaces: 150-300 ft²/gal
 - Spray- 50% of above
- Dry Time @ 70°F:
 - To touch: 1 hour
 - To recoat: 4 hours
- Packaged: 5 gallon containers (55 gallon drums available)

