

EXTREME DUTY

Tar and Other Stubborn Soils

Professional Products **Professional Results**





EXTREME DUTY **CLEANER**





3024-1

EYE CONTACT: Flush with water for at least 15 minutes. If irritation persists, call a physician. SKIN CONTACT: Wash thoroughly with water. If irritation persists, call a physician. Poison Control Center or physician immediately.

INHALATION: Remove to fresh air. Seek medical attention if victim is not responsive. IN CASE OF FIRE Use dry chemical, carbon dioxide, water spray fog or alcohol foam, Closed containers may rupture or explode when heated. Keep cool with water spray.

CONTAINS: Water (7732-18-5), Dipropylene Glycol Methyl Ether (34590-94-8), 2-butoxyethanol (111-76-2), Nonylphenol Ethoxylate (9016-45-9), Sodium Metasilicate Pentahydrate (6834-92-0), Sodium Xylene Sulfonate (1300-72-7), Tetrasodium EDTA (64-02-8), Potassium Hydroxide 1310-58-3, Dye N/A

FIBERLOCK EXTREME DUTY CLEANER 3024 DANGER | DANGER



H290 - May be corrosive to metals

H290 - Peut être corrosif pour les métaux.

H302 - Harmful if swallowed

H302 - Nocif en cas d'ingestion.

H315 - Causes skin irritation.

H315 - Provoque une irritation cutanée.

H318 - Causes serious eye damage.

H318 - Provoque des lésions oculaires graves.

Wear protective gloves/protective clothing/eye protection/face protection.; Keep only in original container.; Do not eat, drink or smoke when using this product.; See SDS for full list of P phrases

Porter des gants de protection/des vêtements de protection/un équipement de protection des veux/du visage. Conserver uniquement dans le récipient d'origine. Ne pas manger, boire ou fumer en manipulant ce produit. Voir SDS pour la liste complète des

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.; Immediately call a POISON CENTER or doctor/ physician.; Specific treatment (see advice on this label).; Take off contaminated clothing and wash before reuse.; Absorb spillage to prevent material damage.; IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.; See SDS for full list of P

EN CAS DE CONTACT AVEC LES YEUX: rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact si la victime en porte et si elles peuvent être facilement enlevées. Continuer à rincer Appeler immédiatement un CENTRE ANTIPOISON ou un médecin.|Traitement spécifique (voir les conseils sur cette étiquette). Enlever les vêtements contaminés et les laver avant réutilisation l'Absorber toute substance répandue pour éviter qu'elle attaque les matériaux environnants. EN CAS D'INGESTION: appeler un CENTRE ANTIPOISON ou un médecin en cas de malaise. Voir SDS pour la liste complète des phrases P

Canadian Contact Info: 4050-B Sladeview Crescent Suite 200 Mississauga, ON L5L 5Y5 Canada



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

DIRECTIONS

damage restoration applications.

Dilute with water to concentration desired for effective cleaning and degreasing as follows:

RECON Extreme Duty Cleaner is one of the most powerful cleaning products available anywhere. Formulated to handle the most extreme cleaning jobs, this high pH, caustic

fortified, butyl based product provides superior ease of use in removing grease, oils, fats,

carbon, wax, tar and other stubborn soils, RECON Extreme Duty Cleaner is a very high

pH butyl cleaner for cleaning and removing the worst deposits in fire, smoke and water

Extreme Duty Cleaning: 16 ounces per gallon of water (1:8) Heavy Duty Cleaning: 8 ounces per gallon of water (1:16) Medium Duty Cleaning: 4 ounces per gallon of water (1:32) General Cleaning: 2 ounces per gallon of water (1:64) 4 ounces per gallon of water (1:32) Steam Cleaning:

Apply with sprayer, sponge, brush or steel wool, agitate as required. Rinse thoroughly with water. Allow to dry or wipe dry on smooth surfaces.

These directions are flexible rather than specific. In many cases a more dilute solution can be used, while for extreme conditions a less dilute solution may be used. Always test substrate in an inconspicuous area to determine if the solution will adversely affect the

PRECAUTIONS

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F (32°C). This cleaner is highly aggressive caustic cleaner. Do not use this product on any surface that could be damaged by a high pH cleaner. Always test substrate in an inconspicuous area to determine if the solution will adversely affect the target material. This product is not intended for use on aluminum, magnesium, zinc or other soft metals. Will degloss painted surfaces. Do not use on glass. Protect floors and surrounding surfaces from contact. Promptly clean off any overspray or dripping from floors.

Container Disposal: Triple rinse container. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by other procedures approved by state and local authorities. Do not contaminate water, food, feed by open dumping of contents. Spill or Leakage Procedure: Contain spill and neutralize with a mild acid. Absorb on inert substance for disposal.

EYE IRRITANT. MAY CAUSE SKIN IRRITATION WITH PROLONGED CONTACT. Avoid contact with skin, eyes, and clothing. Avoid prolonged breathing of concentrated vapors. Avoid breathing of mists. Do not take internally, Harmful if swallowed. Keep out of the reach of children. For professional use only.

INGESTION: Immediately drink large quantities of water. Do not induce vomiting, Call

Extra heavy duty cleaning power

CLEANER

- High pH caustic fortified butyl cleaner Non-flammable
 - Super concentrated and medium foaming

NET CONTENTS: 1 Gallon

For Professional Use Only

Disaster Restoration Products

Removes Grease, Oils, Fats, Carbon, Wax,

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of this product, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at www.fiberlock.com.

Recon™, the Recon™ Logo and other marks in this literature are trademarks of ICP Construction, Inc.



150 Dascomb Rd. Andover, MA 01810 (800) 342-3755 www.fiberlock.com Rev. 10.17.18