

Lag-Kote II is a thick bridging encapsulant/sealant specifically formulated for application over interior friable Asbestos Containing Material (ACM). It is ideally suited to encapsulate interior pipe lagging, boiler jackets, breeching and other components of heating and ventilation systems. Its thick body minimizes dripping, cleanup and product waste while providing a smooth, washable, aesthetically superior finish that will provide years of protection. Lag-Kote II is a flexible coating that can be applied over galvanized metal, wood, masonry or other sound surfaces to prevent the release of harmful asbestos fibers.

SURFACE PREPARATION

Warning! If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

SURFACE REPAIRS & CLEANING

Lagging that is torn, ruptured or delaminated should be repaired with:

1. Patching Cement: Mix cement with water and cap all exposed ends and voids.
2. Lag-Kloth Water-Activated Repair Cloth: Lag-Kloth should be dipped in water and applied to the asbestos containing material.

Upon completion of repairs, prepare the surface for the application of Lag-Kote II. Thoroughly remove all dust and dirt that has accumulated on lagging or covering, use a vacuum with a HEPA filter specifically designed to capture hazardous dust and waste or wipe surfaces with a damp cloth. Do not air clean surfaces; this could increase asbestos exposure.

APPLICATION TOOLS

Apply Lag-Kote II with brush, roller or airless spray equipment.

- Brush: Synthetic, nylon or polyester bristle
Roller: Synthetic fiber 3/8" nap or longer
Spray: .017 to .021 tip @ 2200-2700 PSI.

MIXING

Lag-Kote II may be diluted by adding up to 8 oz. of water per gallon. Prior to application, stir Lag-Kote II thoroughly to achieve a uniform consistency. Lag Kote II can be tinted to pastel colors.

PRODUCT APPLICATION

Select a brush, roller or painter's mitt for convenient application to the ACM. Apply 1-2 coats of Lag-Kote II to the desired film thickness. Minimum film thickness may vary with desired results and type of application.

COVERAGE

Smooth Surfaces: 125-175 ft²/gal.
Porous Surfaces: 75-100 ft²/gal.

DRYING TIME @ 70°F 50% R.H

To Touch: 1-2 hours
Recoat: 8-16 hours

CLEANUP

Tools and drippings should be cleaned with warm soapy water before coating dries. Follow equipment manufacturer's directions to clean spray equipment. Dispose of waste according to all existing local, state and federal regulations.

PRECAUTIONS

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F (32°C). Do not apply at temperatures below 50°F. When applying with a sprayer, wear a NIOSH approved respirator with any R, P, N or HE filter. Approved respirators must be used to prevent inhalation of asbestos fibers that may be present in the air. Protective clothing should be worn.

Asbestos abatement activities must be performed in accordance with all applicable regulations including EPA, OSHA, Federal, State and Local. For more information always contact the appropriate agencies prior to beginning any abatement project.

CAUTION! KEEP OUT OF REACH OF CHILDREN.

Do not take internally. Close container after each use. Keep from freezing. Store between 40°F (4.5°C) and 90°F (32°C) 24 hour Emergency "CHEM-TEL" - 1-800-255-3924

Calculated VOC: 89 g/l



INTERIOR LAGGING ENCAPSULANT

High Build Asbestos Bridging Encapsulant

- Ideal for use on interior pipe lagging, boiler jackets and breeching
- Smooth, washable finish
- Popcorn ceiling and interior transite

NET CONTENTS: 2 Gallons

For Professional Use Only

Asbestos Abatement Products

Professional Products
Professional Results

FIBERLOCK LAG-KOTE II WHITE 6420

WARNING | ATTENTION



H317 - May cause an allergic skin reaction.
H317 - Peut provoquer une allergie cutanée.
H351 - Suspected of causing cancer.
H351 - Susceptible de provoquer le cancer.
H411 - Toxic to aquatic life with long lasting effects.
H411 - Toxique pour les organismes aquatiques, entraîne

Obtain special instructions before use.; Wear protective gloves/protective clothing/ eye protection/face protection.; Use personal protective equipment as required.; Avoid breathing mist/vapours/spray.; Avoid release to the environment.; Contaminated work clothing should not be allowed out of the workplace.; See SDS for full list of P phrases

Se procurer les instructions avant utilisation.; Porter des gants de protection/des vêtements de protection/un équipement de protection des yeux/du visage.; Utiliser l'équipement de protection individuel requis.; Éviter de respirer les brouillards/vapeurs/aérosols.; Éviter le rejet dans l'environnement.; Les vêtements de travail contaminés ne devraient pas sortir du lieu de travail.; Voir SDS pour la liste complète des phrases P

IF exposed or concerned: Get medical advice/attention.; Specific treatment (see advice on this label); Wash contaminated clothing before reuse.; IF ON SKIN: Wash with plenty of soap and water.; If skin irritation or rash occurs: Get medical advice/attention.; Collect spillage.; See SDS for full list of P phrases

EN CAS d'exposition prouvée ou suspectée: Consulter un médecin.; Traitement spécifique (voir les conseils sur cette étiquette); Laver les vêtements contaminés avant réutilisation.; EN CAS DE CONTACT AVEC LA PEAU: laver abondamment à l'eau et au savon.; En cas d'irritation ou d'éruption cutanée: consulter un médecin.; Recueillir le produit répandu.; Voir SDS pour la liste complète des phrases P

Canadian Contact Info:
4050-B Sladeview Crescent Suite 200
Mississauga, ON L5L 5Y5 Canada

⚠️ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of Lag-Kote II, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at www.fiberlock.com.

Lag-Kote II, the Lag-Kote II Logo and other marks on this label are trademarks of ICP Construction, Inc.

6420-2
White



ICP
CONSTRUCTION
150 Dascomb Rd.
Andover, MA 01810
(800) 342-3755
www.fiberlock.com
Rev. 10.16.18