

74 Kent Street Brooklyn, New York 11222-1517 Phone (718) 383-5080 Fax (718) 383-7445 E-mail: dllabs@aol.com

Accredited by National Voluntary Laboratory Accreditation Program - Lab Code 100252 ISO / IEC 17025 and relevant requirements of ISO 9002

June 15, 2005

Fiberlock Technologies, Inc. 150 Dascomb Road Andover, MA 01810-5873

Att: Mr. Andre Weker

Re: DL-14496

Via FAX (976) 475-6205

OBJECTIVE

To evaluate the resistance of a coating to mold and fungal growth.

PRODUCT TESTED

The coating was submitted by Fiberlock Technologies, Inc., for testing and identified as *Aftershock* #8390.

<u>PROCEDURE</u>

The coating's resistance to mold and fungal growth was evaluated in accordance with the procedures outlined in ASTM G 21, "Standard Practice for Determining Resistance of Synthetic Polymeric Materials to Fungi".

The textured coating was cast to produce a free film of 7-mils dry film thickness. The film was allowed to cure a minimum of seven days at standard conditions before testing was initiated. Replicate specimens, measuring 1 X 1-inch were inoculated with a mixed fungal spore suspension consisting of Aspergillus niger, Aureobasidium pullulans, Chaetomium globosum, Gliocladium virens and Penicillium pinophilum.

TEST RESULTS

The Aftershock #8390 coating exhibited a 0-rating for fungal resistance indicating no fungal growth on the surface area of the specimens.

DL Labs. Inc.

Mario Lazaro, Jr.

Assistant Technical Director

cc: M. Lazaro, Jr.