

Fiberlock Piranha NexStrip Pro 5701 Distributed by: GH International Sealants ULC

Version No: 9.10

Safety Data Sheet according to WHMIS 2015 requirements

Issue Date: 02/22/2023 Print Date: 02/22/2023 S.GHS.CAN.EN

SECTION 1 Identification

Product Identifier

Product name	Fiberlock Piranha NexStrip Pro 5701
Synonyms	Not Available
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses Paint Remover

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Distributed by: GH International Sealants ULC	ICP Construction Inc.
Address	2540 Rena Road Mississauga, ON L4T 3C9 Canada	150 Dascomb Road Andover, MA 01810 United States
Telephone	+1-905-677-5522	1-866-667-5119 1-978-623-9987
Fax	Not Available	Not Available
Website	www.icpgroup.com	www.icpgroup.com
Email	sds@icpgroup.com	sds@icpgroup.com

Emergency phone number

Association / Organisation	ChemTel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification Serious Eye Damage/Eye Irritation Category 1, Skin Corrosion/Irritation Category 2

Label elements

Hazard pictogram(s)	
Signal word	Danger

Hazard statement(s)

H318	Causes serious eye damage.
H315	Causes skin irritation.

Physical and Health hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

P280	Wear protective gloves, protective clothing, eye protection and face protection.
P264	Wash all exposed external body areas thoroughly after handling.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/physician/first aider.
P302+P352	IF ON SKIN: Wash with plenty of water.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
100-51-6	35-45	benzyl alcohol
50-21-5	1-5	lactic acid
79-14-1	1-5	glycolic acid

SECTION 4 First-aid measures

Description of first aid measures	
Eye Contact	 If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Clinical experience of benzyl alcohol poisoning is generally confined to premature neonates in receipt of preserved intravenous salines.

- Metabolic acidosis, bradycardia, skin breakdown, hypotonia, hepatorenal failure, hypotension and cardiovascular collapse are characteristic.
- ▶ High urine benzoate and hippuric acid as well as elevated serum benzoic acid levels are found.
- ▶ The so-called "gasping syndrome describes the progressive neurological deterioration of poisoned neonates.
- Management is essentially supportive.

As in all cases of suspected poisoning, follow the ABCDEs of emergency medicine (airway, breathing, circulation, disability, exposure), then the ABCDEs of toxicology (antidotes, basics, change absorption, change distribution, change elimination).

For poisons (where specific treatment regime is absent):

BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 L/min.
- Monitor and treat, where necessary, for pulmonary oedema
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.

• Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.

Positive-pressure ventilation using a bag-valve mask might be of use.

Monitor and treat, where necessary, for arrhythmias.

Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.

Drug therapy should be considered for pulmonary oedema.

+ Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.

Treat seizures with diazepam.

Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

SECTION 5 Fire-fighting measures

Extinguishing media

Foam.

ŝ

- Dry chemical powder.
- BCF (where regulations permit).

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
Special protective equipment a	and precautions for fire-fighters

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course.
Fire/Explosion Hazard	 Combustible. Slight fire hazard when exposed to heat or flame. Acids may react with metals to produce hydrogen, a highly flammable and explosive gas. Combustion products include: carbon dioxide (CO2) aldehydes other pyrolysis products typical of burning organic material. May emit poisonous fumes. WARNING: Long standing in contact with air and light may result in the formation of potentially explosive peroxides.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Slippery when spilt. Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes.
Major Spills	 Slippery when spilt. Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling		
Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. DO NOT allow clothing wet with material to stay in contact with skin 	
Other information	 Store in original containers. Keep containers securely sealed. No smoking, naked lights or ignition sources. 	

Conditions for safe storage, including any incompatibilities

Suitable container	 Lined metal can, lined metal pail/ can. Plastic pail.
--------------------	--

Storage incompatibility	 Polyliner drum. Metal can or drum Packaging as recommende Check all containers are cle Benzyl alcohol: may froth in contact with wa slowly oxidises in air, oxyge is incompatible with minera reacts violently with strong corrodes aluminium at high is incompatible with aluminin attacks some nonfluorinated Benzyl alcohol contaminated with Reacts with mild steel, galv Avoid strong bases. Avoid reaction with oxidisin 	d by manufacturer. early labelled and free from leaks. ater In forming benzaldehyde I acids, caustics, aliphatic amines, iso oxidisers, and explosively with sulfurio temperatures um, iron, steel d plastics; may attack, extract and dis th 1.4% hydrogen bromide and 1.2% anised steel / zinc producing hydroge orides, acid anhydrides and chlorofor g agents	cyanates c acid at elevated temperatu solve polypropylene of dissolved iron(II) polyme n gas which may form an e: mates.	ures rises exothermically above 100 deg. C. xplosive mixture with air.
SECTION 8 Exposure contro Control parameters	ols / personal protection			
Occupational Exposure Limits (OEL)			
INGREDIENT DATA				
Not Available				
	TEEL-1	TEEL 2		TEEL 3
benzyl alcohol	30 ppm	52 ppm		740 ppm
divcolic acid	25 mg/m3	280 mg/m3		390 mg/m3
giyoono dolu	20 mg/m0	200 mg/mo		
Ingredient	Original IDLH		Revised IDLH	
benzyl alcohol	Not Available		Not Available	
lactic acid	Not Available		Not Available	

glycolic acid	

Occupational Exposure Banding

Not Available

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
benzyl alcohol	E	≤ 0.1 ppm
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.	

Not Available

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk.
Individual protection measures, such as personal protective equipment	
Eye and face protection	 Safety glasses with side shields. Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.
Body protection	See Other protection below
Other protection	 Overalls. P.V.C apron. Barrier cream.

Type AB-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Whitepaste		
Physical state	Liquid	Relative density (Water = 1)	1.18
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	4.5	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	>96 (Benzyl Alcohol)	Taste	Not Available
Evaporation rate	Not Available BuAC = 1	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Partly miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	<14 g/L VOC (excluding LVP-VOC)

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. Inhalation of benzyl alcohol may affect breathing (causing depression and paralysis of breathing and lower blood pressure. Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.
Ingestion	The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.

	Swallowing large doses of benzyl alcohol may cause abdominal pain, nausea, vomiting and diarrhea. It may affect behaviour and/or the central nervous system, and cause headache, sleepiness, excitement, dizziness, inco-ordination, coma, convulsions and other symptoms of central nervous system depression.		
	In newborns, exposure to excessive amounts of benzyl alcohol has been and an increased incidence of severe jaundice leading to nervous system	associated with toxicity (low blood pressure and metabolic acidosis), n symptoms called kernicterus.	
	Central nervous system (CNS) depression may include general discomto effects, slowed reaction time, slurred speech and may progress to uncon may be fatal.	rt, symptoms of giddiness, headache, dizziness, nausea, anaesthetic sciousness. Serious poisonings may result in respiratory depression and	
	Accidental ingestion of the material may be harmful; animal experiments produce serious damage to the health of the individual.	indicate that ingestion of less than 150 gram may be fatal or may	
	The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this materia	al	
Skin Contact	Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.		
	Skin contact with the material may be harmful; systemic effects may resu There is some evidence to suggest that the material may cause moderate	It following absorption. e inflammation of the skin either following direct contact or after a delay	
	of some time. Repeated exposure can cause contact dermatitis which is	characterised by redness, swelling and blistering.	
Eye	If applied to the eyes, this material causes severe eye damage.		
Chronic	Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects. Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility. Prolonged or repeated exposure to benzyl alcohol may cause allergic contact dermatitis (skin inflammation). Prolonged or repeated swallowing may affect behaviour and the central nervous system with symptoms similar to acute swallowing. It may also affect the liver, kidneys, cardiovascular system, the lungs and cause weight loss.		
Fiberlock Piranha NexStrip	тохісітү	IRRITATION	
Pro 5701	Not Available	Not Available	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
	B	Eve (rehbit): 0.75 mg enen SEV/ERE	

	Dermal (rabbit) LD50: 2000 mg/kg ^[2]	Eye (rabbit): 0.75 mg open SEVERE
	Inhalation(Rat) LC50: >4.178 mg/L4h ^[2]	Eye: adverse effect observed (irritating) ^[1]
benzyi alconol	Oral (Rat) LD50: 1230 mg/kg ^[2]	Skin (man): 16 mg/48h-mild
		Skin (rabbit):10 mg/24h open-mild
		Skin: no adverse effect observed (not irritating) ^[1]
	ΤΟΧΙΟΙΤΥ	IRRITATION
	Dermal (rabbit) LD50: >2000 mg/kg ^[1]	Eye (rabbit): 0.750 mg SEVERE
lactic acid	Inhalation(Rat) LC50: >7.94 mg/l4h ^[1]	Skin (rabbit): 5 mg/24h SEVERE
	Oral (Rat) LD50: 3543 mg/kg ^[1]	
	ΤΟΧΙΟΙΤΥ	IRRITATION
glycolic acid	Inhalation(Rat) LC50: 3.6 mg/l4h ^[1]	Eye: adverse effect observed (irreversible damage) ^[1]
	Oral (Rat) LD50: 2040 mg/kg ^[1]	Skin: adverse effect observed (corrosive) ^[1]
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute specified data extracted from RTECS - Register of Toxic Effect of che	toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise mical Substances

BENZYL ALCOHOL	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Unlike benzylic alcohols, the beta-hydroxyl group of the members of benzyl alkyl alcohols contributes to break down reactions but do not undergo phase II metabolic activation. Though structurally similar to cancer causing ethyl benzene, phenethyl alcohol is only of negligible concern due to limited similarity in their pattern of activity. For benzoates: Benzyl alcohol, benzoic acid and its sodium and potassium salt have a common metabolic and excretion pathway. All but benzyl alcohol are considered to be unharmful and of low acute toxicity. They may cause slight irritation by oral, dermal or inhalation exposure except sodium benzoate which doesn't irritate the skin. This is a member or analogue of a group of benzyl derivatives generally regarded as safe (GRAS), based partly on their self-limiting properties as flavouring substances in food. In humans and other animals, they are rapidly absorbed, broken down and excreted, with a wide safety margin. The aryl alkyl alcohol (AAA) fragrance ingredients have diverse chemical structures, with similar metabolic and toxicity profiles. The AAA fragrance demonstrate low acute and subchronic toxicity by skin contact and swallowing. At concentrations likely to be encountered by consumers, AAA fragrance ingredients are non-irritating to the skin.
LACTIC ACID	The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.
GLYCOLIC ACID	No significant acute toxicological data identified in literature search. For glycolic acid: Acute toxicity: Glycolic acid (70% solution) is slightly toxic if swallowed. If inhaled, it is moderately toxic. Animal testing shows it is corrosive to the skin and eyes, but does not sensitise the skin.

Fiberlock Piranha NexStrip Pro 5701 & BENZYL ALCOHOL	Adverse reactions to fragrances in perfumes and fragranced cosmetic products include allergic contact dermatitis, irritant contact dermatitis, sensitivity to light, immediate contact reactions, and pigmented contact dermatitis. Airborne and connubial contact dermatitis occurs. Contact allergy is a lifelong condition, so symptoms may occur on re-exposure. Fragrance allergens act as haptens, low molecular weight chemicals that cause an immune response only when attached to a carrier protein. However, not all sensitizing fragrance chemicals are directly reactive, but require previous activation. A prehapten is a chemical that itself causes little or no sensitization, but is transformed into a hapten in the skin (bioactivation), usually via enzyme catalysis.			
BENZYL ALCOHOL & GLYCOLIC ACID	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.			
LACTIC ACID & GLYCOLIC ACID	For simple alpha-hydroxy carbolic acids and their salts: Experimental data available for members of this group shows that they have low acute, repeat-dose, reproductive and developmental toxicity. They are eye and skin irritants, but are not expected to be skin sensitisers. Testing shows they have little or no potential to cause mutations or cancer. For acid mists, aerosols, vapours Test results suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5. Cells from the respiratory tract have not been examined in this respect. Mucous secretion may protect the cells of the airway from direct exposure to inhaled acidic mists (which also protects the stomach lining from the hydrochloric acid secreted there). The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant.			
Acute Toxicity	×	Carcinogenicity	×	
Skin Irritation/Corrosion	✓	Reproductivity	×	
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	×	
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×	
Mutagenicity	×	Aspiration Hazard	×	
		Legend: X – Data either no ✓ – Data available	t available or does not fill the criteria for classification to make classification	

SECTION 12 Ecological information

Fiberlock Piranha NexStrip Pro 5701	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96h	Fish	10mg/l	4
	EC50	72h	Algae or other aquatic plants	500mg/l	2
benzyl alconol	EC50	48h	Crustacea	230mg/l	2
	NOEC(ECx)	336h	Fish	5.1mg/l	2
	EC50	96h	Algae or other aquatic plants	76.828mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50(ECx)	48h	Crustacea	130mg/l	2
lactic acid	LC50	96h	Fish	600mg/l	Not Available
	EC50	72h	Algae or other aquatic plants	>2800mg/L	2
	EC50	48h	Crustacea	130mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	72h	Algae or other aquatic plants	10mg/l	2
glycolic acid	EC50	72h	Algae or other aquatic plants	21.6mg/l	2
	LC50	96h	Fish	164mg/l	2
	EC50	48h	Crustacea	141mg/l	2

Toxic to aquatic organisms.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For benzyl alcohol: log Kow : 1.1Koc : <5Henry's atm m3 /mol: 3.91E-07BOD 5: 1.55-1.6,33-62%COD : 96%ThOD : 2.519BCF : 4

Bioaccumulation: Not significant

Anaerobic Effects: Significant degradation.

Effects on algae and plankton: Inhibits degradation of glucose

Degradation Biological: Significant processes

Abiotic: RxnOH*,no photochem

Ecotoxicity: Fish LC50 (48 h): fathead minnow 770 mg/l; (72 h): 480 mg/l; (96 h) 460 mg/l. Fish LC50 (96 h) fathead minnow 10 ppm, bluegill sunfish 15 ppm; tidewater silverside fish

15 ppm. DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
benzyl alcohol	LOW	LOW
lactic acid	LOW	LOW
glycolic acid	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
benzyl alcohol	LOW (LogKOW = 1.1)
lactic acid	LOW (LogKOW = -0.72)
glycolic acid	LOW (LogKOW = -1.11)

Mobility in soil

Ingredient	Mobility
benzyl alcohol	LOW (KOC = 15.66)
lactic acid	HIGH (KOC = 1)
glycolic acid	HIGH (KOC = 1)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. Recycle wherever possible or consult manufacturer for recycling options. Consult State Land Waste Authority for disposal. Bury or incinerate residue at an approved site.
------------------------------	--

SECTION 14 Transport information

Labels Required NO

Land transport (TDG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
benzyl alcohol	Not Available
lactic acid	Not Available
glycolic acid	Not Available

Transport in bulk in accordance with the IGC Code

Product name	Ship Type
benzyl alcohol	Not Available
lactic acid	Not Available
glycolic acid	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations and the SDS contains all the information required by the Hazardous Products Regulations.

benzyl alcohol is found on the following regulatory lists

Canada Categorization decisions for all DSL substances Canada Domestic Substances List (DSL)

lactic acid is found on the following regulatory lists

Canada Categorization decisions for all DSL substances Canada Domestic Substances List (DSL)

glycolic acid is found on the following regulatory lists Canada Categorization decisions for all DSL substances Canada Domestic Substances List (DSL) Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS

Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS

Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS

National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (benzyl alcohol; lactic acid; glycolic acid)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Initial Date 10/22/2017	

CONTACT POINT

PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES

SDS Version Summary

Version	Date of Update	Sections Updated
8.10	02/14/2023	Composition / information on ingredients - Ingredients, Physical and chemical properties - Physical Properties

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios.

Powered by AuthorITe, from Chemwatch.