

Piranha 4 is a solvent-based gel formulated to remove multiple layers of paint. Piranha 4 starts removing most paints and stubborn coatings in less than one hour, without the use of chlorinated solvents, caustics or methylene chloride. The gel formulation yields maximum coverage per gallon and has excellent resistance to sagging, enabling it to cling to vertical and overhead surfaces. Piranha 4 has a very slow rate of evaporation keeping it active for hours. Piranha 4 is a unique solvent formulation ideally suited for paint removal from historically significant architectural components since it does not discolor or raise wood grain or require neutralization. Piranha 4 can be used on virtually any substrate to remove oil-based paints, latex paints, elastomeric paints, cementitious asbestos paints, epoxies and urethanes.

#### SURFACE PREPARATION

Warning! If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

Protect all surfaces not being stripped with polyethylene sheeting. For interior use, open windows and doors or use other means to assure a constant supply of fresh moving air during use. Ideal working temperature is between 65-85°F; not recommended when substrate temperature is below 60°F. Avoid direct sunlight.

#### APPLICATION TOOLS

Apply Piranha 4 with brush, roller or airless spray equipment.

- Brush: Synthetic, nylon or polyester bristle
- Roller: Synthetic fiber 3/8" nap or longer
- Spray: .019 to .021 tip

#### PRODUCT APPLICATION

For best results, perform a test patch to determine the appropriate dwell time required to remove the existing paint system. The length of time required to remove a paint system is dependent on the application temperature, and the thickness and type of paint being stripped. If Piranha 4 is to be left for an extended period of time, cover with polyethylene sheeting. Piranha 4 can be applied using a brush, roller or airless sprayer.

Be certain that all uneven or irregular surfaces receive adequate coverage. When Piranha 4 has penetrated to the substrate, scrape the softened paint residue.

Clean substrate with mild detergent solution. All Piranha 4 residues should be fully removed prior to repainting.

#### COVERAGE

- Smooth Surfaces: 125 ft<sup>2</sup>/gal.
- Porous Surfaces: 50-100 ft<sup>2</sup>/gal.

#### CLEANUP

Clean tools and drippings with warm soapy water. Collect all waste in a plastic bag or drum. Properly dispose of waste and wastewater in accordance with all local, state and federal regulations. Keep container closed when not in use. If practical, filter wastewater in accordance with a federally or locally accepted method to minimize the amount of waste which must be disposed of as hazardous.

#### PRECAUTIONS

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F (32°C). Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protective clothing should be worn. Wear rubber gloves. Wear eye protection at all times. Face and head protection should be worn when working at face level or overhead. Dispose of contents/container in accordance with local/regional/national/international regulations.

#### FIRST AID

EYE: Immediately flush eyes with plenty of water for at least 15 minutes while holding eyes open. Get medical attention.

SKIN: Remove contaminated clothing and shoes. Flush skin with water. Follow by washing skin thoroughly with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned.

INGESTION: If ingested, DO NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs. Get medical attention.

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing.

SUPPLEMENT HEALTH INFORMATION: Overexposure may cause blurring vision.

#### CAUTION!

**KEEP OUT OF REACH OF CHILDREN.  
FOR PROFESSIONAL APPLICATORS ONLY!  
OVER EXPOSURE MAY CAUSE BLURRING OF  
VISION.**

- Do not take internally.
- Close container after each use.
- Keep from freezing.

Store between 40°F (4.5°C) and 90°F (32°C)  
24 hour Emergency "CHEM-TEL" - 1-800-255-3924



Professional Products  
Professional Results



GEL PAINT STRIPPER



For Use On All Types of Wood, Metal and  
Masonry. Ideal for Historical Structures

- Does Not Contain Chlorinated Solvents, Caustics, or Methylene Chloride
- Slow Evaporation Rate
- Excellent Resistance to Sagging

NET CONTENTS: 5 Gallons

For Professional Use Only

Paint Removal Products

FIBERLOCK PIRANHA 4 5740  
DANGER | DANGER



H227 - Combustible liquid.  
H319 - Causes serious eye irritation.  
H360 - May damage fertility or the unborn child.  
H371 - May cause damage to organs.

Obtain special instructions before use.; Keep away from heat/sparks/open flames/hot surfaces. - No smoking.; Do not breathe dust/fume/gas/mist/vapours/spray.; Use personal protective equipment as required.; Do not eat, drink or smoke when using this product.; Wear protective gloves/protective clothing/eye protection/face protection.; See SDS for full list of P phrases

IF exposed or concerned: Get medical advice/attention.; IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.; In case of fire: Use water jets for extinction.; IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.; If eye irritation persists: Get medical advice/attention.; See SDS for full list of P phrases

Canadian Contact Info:  
4050-B Sladeview Crescent Suite 200  
Mississauga, ON L5L 5Y5 Canada

⚠ **WARNING:** Cancer and Reproductive Harm -  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Calculated VOC: Below 520 g/l

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at [www.fiberlock.com](http://www.fiberlock.com).

Piranha, the Piranha Logo and other marks on this label are trademarks of ICP Construction, Inc.

5740-5



150 Dascomb Rd.  
Andover, MA 01810  
(800) 342-3755  
[www.fiberlock.com](http://www.fiberlock.com)  
Rev. 10.17.18