

# Fiberlock Lag-Kote II White 6420

# ICP Building Solutions Group (CAN)

Version No: 8.10

Safety Data Sheet according to WHMIS 2015 requirements

Issue Date: 01/22/2020 Print Date: 01/31/2020 S.GHS.CAN.EN

## **SECTION 1 IDENTIFICATION**

#### **Product Identifier**

Product name	Fiberlock Lag-Kote II White 6420
Synonyms	Not Available
Other means of identification	Not Available

#### Recommended use of the chemical and restrictions on use

Relevant identified uses Asbestos Encapsulant

## Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Building Solutions Group (CAN)	
Address	5 Bay St. North Hamilton, Ontario L8L 1H1 Canada	
Telephone	978-623-9980	
Fax	Not Available	
Website	www.icpgroup.com	
Email	Not Available	

#### **Emergency phone number**

Association / Organisation	Chemtel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

## **SECTION 2 HAZARD(S) IDENTIFICATION**

## Classification of the substance or mixture

#### NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Eye Irritation Category 2A, Specific target organ toxicity - repeated exposure Category 2, Acute Aquatic Hazard Category 3, Skin Corrosion/Irritation Category 2, Carcinogenicity Category 1A, Skin Sensitizer Category 1, Germ cell mutagenicity Category 2, Chronic Aquatic Hazard Category 3

## Label elements

Hazard pictogram(s)





SIGNAL WORD

Hazard statement(s)		
H319	Causes serious eye irritation.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H315	Causes skin irritation.	
H350	May cause cancer.	

Version No: 8.10 Page 2 of 11 Issue Date: 01/22/2020 Print Date: 01/31/2020

## Fiberlock Lag-Kote II White 6420

H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.
H412	Harmful to aquatic life with long lasting effects.

#### Physical and Health hazard(s) not otherwise classified

Not Applicable

## Precautionary statement(s) General

P101	medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	

## Precautionary statement(s) Prevention

P201	Obtain special instructions before use.	
P260	Do not breathe mist/vapours/spray.	

## Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/ attention.	
P321	Specific treatment (see advice on this label).	

## Precautionary statement(s) Storage

P405 Store locked up.

## Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

#### Substances

See section below for composition of Mixtures

## Mixtures

CAS No	%[weight]	Name
57-55-6	1-5	propylene glycol
1897-45-6	<1	chlorothalonil
124-68-5	.5-5	monoisobutanolamine
13463-67-7	5-15	titanium dioxide
1332-58-7	10-15	kaolin
25265-77-4	.5-5	2.2.4-trimethyl-1.3-pentanediol monoisobutyrate
1314-13-2	1-5	zinc oxide

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

## **SECTION 4 FIRST-AID MEASURES**

## Description of first aid measures

Eye Contact	If this product comes in contact with the eyes:  Wash out immediately with fresh running water.  Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  Seek medical attention without delay; if pain persists or recurs seek medical attention.  Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs:  Immediately remove all contaminated clothing, including footwear.  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion  ► Immediately give a glass of water.  ► First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.	

## Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## **SECTION 5 FIRE-FIGHTING MEASURES**

Version No: 8.10 Page 3 of 11 Issue Date: 01/22/2020 Print Date: 01/31/2020

## Fiberlock Lag-Kote II White 6420

**Extinguishing media** 

- ► Foam.
- Dry chemical powder.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility

▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

#### Special protective equipment and precautions for fire-fighters

Fire Fighting

- ▶ Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus.

▶ Combustible.

▶ Slight fire hazard when exposed to heat or flame.

Combustion products include:

Fire/Explosion Hazard

carbon dioxide (CO2) other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

## **SECTION 6 ACCIDENTAL RELEASE MEASURES**

## Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

## Methods and material for containment and cleaning up

Minor Spills	Environmental hazard - contain spillage.  • Remove all ignition sources.  • Clean up all spills immediately.
Major Spills	Environmental hazard - contain spillage.  Moderate hazard.  Clear area of personnel and move upwind.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

#### **SECTION 7 HANDLING AND STORAGE**

## Precautions for safe handling

Safe handling	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>DO NOT allow clothing wet with material to stay in contact with skin</li> </ul>
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> </ul>

## Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Metal can or drum</li> <li>Packaging as recommended by manufacturer.</li> <li>Check all containers are clearly labelled and free from leaks.</li> </ul>
Storage incompatibility	Titanium dioxide  • reacts with strong acids, strong oxidisers  • reacts violently with aluminium, calcium, hydrazine, lithium (at around 200 deg C.), magnesium, potassium, sodium, zinc, especially at elevated temperatures - these reactions involves reduction of the oxide and are accompanied by incandescence  • dust or powders can ignite and then explode in a carbon dioxide atmosphere  • Avoid reaction with oxidising agents

# **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

## **Control parameters**

## OCCUPATIONAL EXPOSURE LIMITS (OEL)

# INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Ontario Occupational Exposure Limits	propylene glycol	1,2-Propylene glycol	50 ppm / 155; 10 mg/m3	Not Available	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	titanium dioxide	Titanium dioxide	10 mg/m3	Not Available	Not Available	TLV Basis: lower respiratory tract irritation

Version No: 8.10 Page 4 of 11 Issue Date: 01/22/2020 Print Date: 01/31/2020

Fiberlock Lag-Kote II White 6420

	ı	ı	1	ı	1	1
Canada - Alberta Occupational Exposure Limits	titanium dioxide	Titanium dioxide	10 mg/m3	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	titanium dioxide	Titanium dioxide	10 mg/m3	20 mg/m3	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	titanium dioxide	Not Available	10 mg/m3	Not Available	Not Available	TLV® Basis: LRT irr
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	titanium dioxide	Titanium dioxide	10 mg/m3	Not Available	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits (English)	titanium dioxide	Titanium dioxide	10 mg/m3	20 mg/m3	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	titanium dioxide	Titanium dioxide	10 mg/m3	Not Available	Not Available	(N) - the 8-hour TWA listed in the Table is for the total dust. The substance also has an 8-hour TWA of 3 mg/m 3 for the respirable fraction.
Canada - Prince Edward Island Occupational Exposure Limits	titanium dioxide	Titanium dioxide	10 mg/m3	Not Available	Not Available	TLV® Basis: LRT irr
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	kaolin	Kaolin	Not Available	Not Available	Not Available	(See Table 11)
Canada - Nova Scotia Occupational Exposure Limits	kaolin	Kaolin	2 mg/m3	Not Available	Not Available	TLV Basis: pneumoconiosis. Value is for particulate matter containing no asbestos and <1% crystalline silica.
Canada - Alberta Occupational Exposure Limits	kaolin	Kaolin respirable	2 mg/m3	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	kaolin	Kaolin (respirable fraction++ )	2 mg/m3	4 mg/m3	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	kaolin	Not Available	2 mg/m3	Not Available	Not Available	TLV® Basis: Pneumoconiosis
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	kaolin	Kaolin	5 mg/m3	Not Available	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits (English)	kaolin	Kaolin (respirable fraction)	2 mg/m3	4 mg/m3	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	kaolin	Kaolin, Respirable	2 mg/m3	Not Available	Not Available	(E) - the value is for particulate matter containing no asbestos and less than 1% crystalline silica.
Canada - Prince Edward Island Occupational Exposure Limits	kaolin	Kaolin	2 mg/m3	Not Available	Not Available	TLV® Basis: Pneumoconiosis
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	zinc oxide	Zinc oxide dust	Not Available	Not Available	Not Available	(See Table 11)
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	zinc oxide	Zinc oxide fume	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	zinc oxide	Zinc oxide	2 mg/m3	10 mg/m3	Not Available	TLV Basis: metal fume fever
Canada - Alberta Occupational Exposure Limits	zinc oxide	Zinc oxide, respirable	2 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	zinc oxide	Zinc oxide, fume and dust (respirable fraction++)	2 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	zinc oxide	Not Available	2 mg/m3	10 mg/m3	Not Available	TLV® Basis: Metal fume fever
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	zinc oxide	Zinc, oxide	Not Available	Not Available	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	zinc oxide	Zinc, oxide: Fume	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	zinc oxide	Zinc, oxide: Dust	10 mg/m3	Not Available	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits (English)	zinc oxide	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Respirable fraction	3 mg/m3	6 mg/m3	Not Available	Not Available

Version No: 8.10 Page **5** of **11** Issue Date: 01/22/2020 Print Date: 01/31/2020

## Fiberlock Lag-Kote II White 6420

Canada - Northwest Territories Occupational Exposure Limits (English)	zinc oxide	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Inhalable fraction	10 mg/m3	20 mg/m3	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	zinc oxide	Zinc oxide, Respirable	2 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	zinc oxide	Zinc oxide	2 mg/m3	10 mg/m3	Not Available	TLV® Basis: Metal fume fever
Canada - Ontario Occupational Exposure Limits	zinc oxide	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified (PNOS)	10; 3 mg/m3	Not Available	Not Available	Not Available

## **EMERGENCY LIMITS**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
propylene glycol	Polypropylene glycols	30 mg/m3	330 mg/m3	2,000 mg/m3
propylene glycol	Propylene glycol; (1,2-Propanediol)	30 mg/m3	1,300 mg/m3	7,900 mg/m3
chlorothalonil	Chlorothalonil; (Tetrachloroisophthalonitrile)	0.13 mg/m3	1.4 mg/m3	8.6 mg/m3
monoisobutanolamine	Isobutanol-2-amine	17 mg/m3	190 mg/m3	570 mg/m3
titanium dioxide	Titanium oxide; (Titanium dioxide)	30 mg/m3	330 mg/m3	2,000 mg/m3
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	Trimethyl-1,3-pentanediol monoisobutyrate, 2,2,4-; (Texanol)	13 mg/m3	140 mg/m3	840 mg/m3
zinc oxide	Zinc oxide	10 mg/m3	15 mg/m3	2,500 mg/m3

Ingredient	Original IDLH	Revised IDLH
propylene glycol	Not Available	Not Available
chlorothalonil	Not Available	Not Available
monoisobutanolamine	Not Available	Not Available
titanium dioxide	5,000 mg/m3	Not Available
kaolin	Not Available	Not Available
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	Not Available	Not Available
zinc oxide	500 mg/m3	Not Available

## OCCUPATIONAL EXPOSURE BANDING

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit	
chlorothalonil	E	≤ 0.01 mg/m³	
monoisobutanolamine	E	≤ 0.01 mg/m³	
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.		

## **Exposure controls**

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls cabe highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
Personal protection	
Eye and face protection	Safety glasses with side shields.     Chemical goggles.
Skin protection	See Hand protection below
Hands/feet protection	<ul> <li>Wear chemical protective gloves, e.g. PVC.</li> <li>Wear safety footwear or safety gumboots, e.g. Rubber</li> <li>NOTE:</li> <li>The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</li> <li>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</li> </ul>
Body protection	See Other protection below
Other protection	► Overalls. ► P.V.C.

#### Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
   The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge

Version No: 8.10 Page 6 of 11 Issue Date: 01/22/2020 Print Date: 01/31/2020

## Fiberlock Lag-Kote II White 6420

respirators is considered appropriate.

F Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

## **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

## Information on basic physical and chemical properties

Appearance	Text		
Physical state	Lianid	Relative density (Water = 1)	Not Available
Physical state	Liquid	Relative defisity (water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	8.5	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

## **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

## **SECTION 11 TOXICOLOGICAL INFORMATION**

## Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	Ingestion of propylene glycol produced reversible central nervous system depression in humans following ingestion of 60 ml. Symptoms included increased heart-rate (tachycardia), excessive sweating (diaphoresis) and grand mal seizures in a 15 month child who ingested large doses (7.5 ml/day for 8 days) as an ingredient of vitamin preparation.  The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	This material can cause inflammation of the skin on contact in some persons.  The material may accentuate any pre-existing dermatitis condition  Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	This material can cause eye irritation and damage in some persons.
Chronic	Studies show that inhaling this substance for over a long period (e.g. in an occupational setting) may increase the risk of cancer.  Strong evidence exists that this substance may cause irreversible mutations (though not lethal) even following a single exposure.  Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.  Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.  This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.

Version No: 8.10 Page **7** of **11** Issue Date: 01/22/2020 Print Date: 01/31/2020

## Fiberlock Lag-Kote II White 6420

Chronic dust inhalation of kaolin, can cause kaolinosis from kaolin deposition in the lungs causing distinct lung markings, abnormal inflation of air sacs, and chronic lung diseases (nodular pneumoconiosis). This condition is made worse by long duration of occupational exposure and pre-existing chest infection. Pre-employment screening is recommended.

Propylene glycol is thought to be sensitizing following the regular use of topical creams by eczema patients. Testing in humans showed that 16% of exposed individuals, irritation occurred, with 12.5% showing toxic or allergic reactions.

	of exposed individuals, irritation occurred, with 12.5% showing	ing toxic or allergic reactions.	
Fiberlock Lag-Kote II White	TOXICITY	IRRITATION	
6420	Not Available	Not Available	
	TOXICITY	IRRITATION	
	Dermal (rabbit) LD50: 11890 mg/kg <sup>[2]</sup>	Eye (rabbit): 100 mg - mild	
	Inhalation (rat) LC50: >44.9 mg/l/4H <sup>[2]</sup>	Eye (rabbit): 500 mg/24h - mild	
propylene glycol	Oral (rat) LD50: 20000 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>	
propylene grycor	Oral (rat) ED30. 20000 Hig/kgt 7	Skin(human):104 mg/3d Intermit Mod	
		Skin(human):500 mg/7days mild	
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
	TOXICITY	IRRITATION	
	dermal (rat) LD50: >2500 mg/kg <sup>[2]</sup>	Not Available	
chlorothalonil	Inhalation (rat) LC50: 0.0775 mg/l/1h <sup>[2]</sup>		
	Oral (rat) LD50: >5000 mg/kg <sup>[2]</sup>		
	TOXICITY	IRRITATION	
monoisobutanolamine	Dermal (rabbit) LD50: >2000 mg/kg <sup>[2]</sup>	Not Available	
	Oral (rat) LD50: 2900 mg/kg <sup>[2]</sup>		
	TOXICITY	IRRITATION	
	dermal (hamster) LD50: >=10000 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>	
titanium dioxide	Oral (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Skin (human): 0.3 mg /3D (int)-mild *	
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
lea allea	TOXICITY	IRRITATION	
kaolin	Not Available	Not Available	
	TOXICITY	IRRITATION	
	Dermal (rabbit) LD50: >15200 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>	
2,4-trimethyl-1,3-pentanediol	Inhalation (rat) LC50: >5.325 mg/l/6h[2]	Eyes - Moderate irritant *	
monoisobutyrate	Oral (rat) LD50: 3200 mg/kg <sup>[2]</sup>	Skin - Slight irritant *	
		Skin (rabbit): mild ***	
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
	TOXICITY	IRRITATION	
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye (rabbit) : 500 mg/24 h - mild	
zinc oxide	Inhalation (rat) LC50: >1.79 mg/l4 h <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>	
	Oral (rat) LD50: >5000 mg/kg <sup>[2]</sup>	Skin (rabbit) : 500 mg/24 h- mild	
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
Legend:	Nalue obtained from Europe ECHA Registered Substanct     specified data extracted from RTECS - Register of Toxic Eff	es - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise fect of chemical Substances	
CHI ODOTUAL ONII	Chlorothalanii has law taviaity according to animal tasting	t irritates the skin and eve. ADI: 0.04 malkalday NOCL: 4.5 malkalday.	
CHLOROTHALONIL		t irritates the skin and eye. ADI: 0.01 mg/kg/day NOEL: 1.5 mg/kg/day  any, toxicity. They are mildly irritating to eyes at moderate concentrations, and do no	
MONOISOBUTANOLAMINE	cause allergic skin reactions.	any, toxiony. They are finially initiating to eyes at moderate seriositiations, and de n	
TITANIUM DIOXIDE	* IUCLID  Exposure to titanium dioxide is via inhalation, swallowing or skin contact. When inhaled, it may deposit in lung tissue and lymph nodes causing dysfunction of the lungs and immune system. Absorption by the stomach and intestines depends on the size of the particle.  The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.		
KAOLIN	For bentonite clays: Bentonite (CAS No. 1302-78-9) consists of a group of clays formed by crystallization of vitreous volcanic ashes that were deposited in water. The expected acute oral toxicity of bentonite in humans is very low.		
2,2,4-TRIMETHYL- 1,3-PENTANEDIOL	Not a skin sensitiser (guinea pig, Magnusson-Kligman) *** Ames Test: negative *** Micronucleus, mouse: negative *** Not mutagenic *** No effects on fertility or foetal development seen in the rat *** * [SWIFT] ** [Eastman] *** [Perstop]  The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce		

MONOISOBUTYRATE

conjunctivitis.

Version No: 8.10 Page 8 of 11 Issue Date: 01/22/2020

## Fiberlock Lag-Kote II White 6420

Print Date: 01/31/2020

Fiberlock Lag-Kote II White 6420 & TITANIUM DIOXIDE	Laboratory (in vitro) and animal studies show, exposure to the material may result in a possible risk of irreversible effects, with the possibility of producing mutation.			
Fiberlock Lag-Kote II White 6420 & CHLOROTHALONIL	The following information refers to contact allergens as a group and may not be specific to this product.  Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type.			
Fiberlock Lag-Kote II White 6420 & PROPYLENE GLYCOL	The acute oral toxicity of propylene glycol is very low; large amounts are needed to cause perceptible health damage in humans. Serious toxicity generally occurs only at blood concentrations over 1 g/L, which requires extremely high intake over a relatively short period of time; this is nearly impossible with consuming foods or supplements which contain 1g/kg of PG at most.			
PROPYLENE GLYCOL & TITANIUM DIOXIDE & 2,2,4- TRIMETHYL- 1,3-PENTANEDIOL MONOISOBUTYRATE & ZINC OXIDE	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.			
CHLOROTHALONIL & TITANIUM DIOXIDE	Asthma-like symptoms may continue for months or ev known as reactive airways dysfunction syndrome (RA WARNING: This substance has been classified by the	DS) which can occur after exposure to	o high levels of highly irritating compound.	
TITANIUM DIOXIDE & KAOLIN	No significant acute toxicological data identified in liter	rature search.		
Acute Toxicity	×	Carcinogenicity	<b>~</b>	
Skin Irritation/Corrosion	~	Reproductivity	×	
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	×	
Respiratory or Skin sensitisation	•	STOT - Repeated Exposure	<b>~</b>	
Mutagenicity	✓	Aspiration Hazard	×	

Legend:

X − Data either not available or does not fill the criteria for classification
 ✓ − Data available to make classification

## **SECTION 12 ECOLOGICAL INFORMATION**

## Toxicity

Fiberlock Lag-Kote II White 6420	ENDPOINT	TEST DURATION (HR)	SPECIES	VAL	JE	SOURCE
	Not Available	Not Available	Not Available	Not Avai	able	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES VALUE			SOURCE
	LC50	96	Fish >10-mg/L		/L	2
propylene glycol	EC50	48	Crustacea 43-500mg/L		2	
	EC50	96	Algae or other aquatic plants 19-mg/L		2	
	NOEC	168	Fish	11-530r	ng/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE		SOURC
	LC50	96	Fish	0.0076mg/l	-	4
	EC50	48	Crustacea	0.0066475	ng/L	4
chlorothalonil	EC50	72	Algae or other aquatic plants	0.0068mg/l	-	4
	BCF	336	Algae or other aquatic plants 0.02mg/L			4
	NOEC	240	Crustacea 0.0003mg/L		4	
	ENDPOINT	TEST DURATION (HR)	SPECIES VALUE			SOURC
	LC50	96	Fish =100mg/L		g/L	1
monoisobutanolamine	EC50	48	Crustacea =193mg/L		g/L	1
	EC50	96	Algae or other aquatic plants 52.872mg/L		3	
	NOEC	48	Crustacea 100mg/L		2	
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALU	E	SOURC
	LC50	96	Fish	Fish >1-mg/L		2
titanium dioxide	EC50	48	Crustacea >1-mg/L		/L	2
	EC50	72	Algae or other aquatic plants 5.83mg/L		g/L	4
	NOEC	336	Fish 0.089mg/L		ng/L	4
	ENDPOINT	TEST DURATION (HR)	SPECIES VALUE		JE	SOURC
kaolin	Not Available	Not Available	Not Available	Not Avai	able	Not Available
.,4-trimethyl-1,3-pentanediol	ENDPOINT	TEST DURATION (HR)	SPECIES	VALU	E	SOURC
monoisobutyrate	LC50	96	Fish	9.552	na/L	3

Version No: **8.10** Page **9** of **11** Issue Date: **01/22/2020** 

## Fiberlock Lag-Kote II White 6420

Print Date: 01/31/2020	

EC50		48	Crustacea	>19mg/L	2
	EC50	96	Algae or other aquatic plants	0.789mg/L	3
	NOEC	72	Algae or other aquatic plants	2mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	0.001-0.58mg/L	2
	EC50	48	Crustacea	0.001-0.014mg/L	2
zinc oxide	EC50	72	Algae or other aquatic plants	0.037mg/L	2
	BCF	336	Fish	4376.673mg/L	4
	NOEC	72	Algae or other aquatic plants	0.00008138mg/L	2

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Bentonite and kaolin have low toxicity to aquatic species, a large number of which have been tested

Propylene glycol is known to exert high levels of biochemical oxygen demand (BOD) during degradation in surface waters. This process can adversely affect aquatic life by consuming oxygen needed by aquatic organisms for survival.

DO NOT discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
propylene glycol	LOW	LOW
chlorothalonil	HIGH	HIGH
monoisobutanolamine	LOW	LOW
titanium dioxide	HIGH	HIGH
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	LOW	LOW

## **Bioaccumulative potential**

Ingredient	oaccumulation	
propylene glycol	W (BCF = 1)	
chlorothalonil	LOW (BCF = 125)	
monoisobutanolamine	LOW (BCF = 330)	
titanium dioxide	LOW (BCF = 10)	
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	LOW (LogKOW = 2.9966)	
zinc oxide	LOW (BCF = 217)	

## Mobility in soil

Ingredient	obility		
propylene glycol	GH (KOC = 1)		
chlorothalonil	LOW (KOC = 2392)		
monoisobutanolamine	MEDIUM (KOC = 2.196)		
titanium dioxide	LOW (KOC = 23.74)		
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	LOW (KOC = 22.28)		

## **SECTION 13 DISPOSAL CONSIDERATIONS**

## Waste treatment methods

- ► Containers may still present a chemical hazard/ danger when empty.
- Return to supplier for reuse/ recycling if possible.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

#### Product / Packaging disposal

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- ▶ It may be necessary to collect all wash water for treatment before disposal.
- Recycle wherever possible or consult manufacturer for recycling options.
   Consult State Land Waste Authority for disposal.

# SECTION 14 TRANSPORT INFORMATION

# Labels Required

Version No: 8.10 Page 10 of 11 Issue Date: 01/22/2020 Print Date: 01/31/2020

#### Fiberlock Lag-Kote II White 6420

Marine Pollutant

NO

Land transport (TDG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### **SECTION 15 REGULATORY INFORMATION**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled **Products Regulations** 

#### PROPYLENE GLYCOL IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada - Ontario Occupational Exposure Limits

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information

System - WHMIS GHS (English)

GESAMP/EHS Composite List - GESAMP Hazard Profiles

#### CHLOROTHALONIL IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada - Saskatchewan Occupational Health and Safety Regulations - Designated Chemical Substances

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Transport Dangerous Goods - Schedule 1

Canada Transport Dangerous Goods - Schedule 3

Chemical Footprint Project - Chemicals of High Concern List

IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk

IMO IBC Code Chapter 18: List of products to which the Code does not apply

IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances

IMO IBC Code Chapter 17: Summary of minimum requirements

IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs International Agency for Research on Cancer (IARC) - Agents Classified by the IARC

Monographs - Group 2B: Possibly carcinogenic to humans

International Air Transport Association (IATA) Dangerous Goods Regulations

International Maritime Dangerous Goods Requirements (IMDG Code)

United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

## MONOISOBUTANOLAMINE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada Categorization decisions for all DSL substances

System - WHMIS GHS (English)

GESAMP/EHS Composite List - GESAMP Hazard Profiles IMO IBC Code Chapter 17: Summary of minimum requirements

IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk

#### TITANIUM DIOXIDE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada - Alberta Occupational Exposure Limits

Canada - British Columbia Occupational Exposure Limits

Canada - Manitoba Occupational Exposure Limits

Canada - Northwest Territories Occupational Exposure Limits

Canada - Nova Scotia Occupational Exposure Limits

Canada - Prince Edward Island Occupational Exposure Limits

Canada - Quebec Permissible Exposure Values for Airborne Contaminants

Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Non-Domestic Substances List (NDSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS (English)

Chemical Footprint Project - Chemicals of High Concern List

GESAMP/EHS Composite List - GESAMP Hazard Profiles IMO IBC Code Chapter 17: Summary of minimum requirements

IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B : Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

#### KAOLIN IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada - Alberta Occupational Exposure Limits

Canada - British Columbia Occupational Exposure Limits

Canada - Manitoba Occupational Exposure Limits

Canada - Northwest Territories Occupational Exposure Limits

Canada - Nova Scotia Occupational Exposure Limits

Canada - Prince Edward Island Occupational Exposure Limits

Canada - Quebec Permissible Exposure Values for Airborne Contaminants

Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits

Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS (English)

Chemical Footprint Project - Chemicals of High Concern List

GESAMP/EHS Composite List - GESAMP Hazard Profiles

IMO IBC Code Chapter 18: List of products to which the Code does not apply International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

## 2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information

System - WHMIS GHS (English)

GESAMP/EHS Composite List - GESAMP Hazard Profiles IMO IBC Code Chapter 17: Summary of minimum requirements IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk

## ZINC OXIDE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Version No: **8.10** Page **11** of **11** Issue Date: **01/22/2020** 

## Fiberlock Lag-Kote II White 6420

Print Date: 01/31/2020

Canada - Alberta Occupational Exposure Limits
Canada - British Columbia Occupational Exposure Limits
Canada - Manitoba Occupational Exposure Limits
Canada - Northwest Territories Occupational Exposure Limits
Canada - Nova Scotia Occupational Exposure Limits
Canada - Ontario Occupational Exposure Limits
Canada - Prince Edward Island Occupational Exposure Limits
Canada - Quebec Permissible Exposure Values for Airborne Contaminants
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination
Limits

Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances

Canada Domestic Substances List (DSL)
Canada Non-Domestic Substances List (NDSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS (English)

Canada Transport Dangerous Goods - Schedule 1 Canada Transport Dangerous Goods - Schedule 3

Canada Categorization decisions for all DSL substances

International Air Transport Association (IATA) Dangerous Goods Regulations

International Maritime Dangerous Goods Requirements (IMDG Code)

United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

## **National Inventory Status**

National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (chlorothalonil; monoisobutanolamine; kaolin; propylene glycol; 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (kaolin)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - ARIPS	No (chlorothalonil)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

#### **SECTION 16 OTHER INFORMATION**

Revision Date	01/22/2020
Initial Date	08/30/2017

## CONTACT POINT

\*\*PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES\*\*

#### **SDS Version Summary**

Version	Issue Date	Sections Updated
7.10.1.1.1	01/22/2020	Acute Health (eye), Acute Health (skin), Acute Health (swallowed), Chronic Health, Classification, Disposal, Environmental, Exposure Standard, Fire Fighter (extinguishing media), Fire Fighter (fire/explosion hazard), Fire Fighter (fire fighting), Fire Fighter (fire incompatibility), First Aid (eye), Handling Procedure, Ingredients, Personal Protection (Respirator), Spills (major), Spills (minor), Storage (storage incompatibility), Storage (storage requirement), Storage (suitable container), Supplier Information

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

## **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value BCF: BioConcentration Factors

BEI: Biological Exposure Index

Powered by AuthorlTe, from Chemwatch.