

Lag-Kloth is a woven fabric impregnated with an inorganic adhesive, designed to repair and/or cover existing asbestos insulation on pipes, boilers and breeching. Areas that are repaired or re-covered with Lag-Kloth can be successfully top coated with Lag-Kote®, Lag-Kote II or SerpiMastic for complete encapsulation. The self-contained adhesive in Lag-Kloth is water activated and non-flammable. Lag-Kloth can withstand temperatures up to 600°F.

SURFACE PREPARATION

Prior to application it is important to determine if the existing asbestos matrix is well adhered to the substrate. Correct any surface defects and clean all surfaces thoroughly. Be careful not to agitate asbestos fibers during preparation; this could increase asbestos exposure.

Locate damaged asbestos containing thermal insulation. Thoroughly remove all dust and dirt that has accumulated on lagging or covering, using a vacuum with a HEPA filter specifically designed to capture hazardous dust and waste or wipe surfaces with a damp cloth. Do not air clean surfaces; this could increase asbestos exposure. Heavy rust should be scraped or wire-brushed from all ferrous metal surfaces or hangers before vacuuming surrounding surfaces. Wetting exposed insulation with Fiberlock’s Penewet wetting agent will help suppress the release of asbestos fibers.

PRODUCT APPLICATION

Do not apply Lag-Kloth to surfaces hotter than 120°F at time of application. After Lag-Kloth has cured it can withstands temperatures up to 600°F. Cut Lag-Kloth to appropriate size. Dip Lag-Kloth in water and smooth out excess water (DO NOT WRING OUT). Shape Lag-Kloth to specific area by hand and apply to surface. Overlap loose ends of Lag-Kloth to ensure complete coverage. Allow Lag-Kloth to dry before applying Lag-Kote, Lag-Kote II or SerpiMastic bridging agents.

DRYING TIME

- Hot insulation: 2-4 hours
- Cold insulation: 8-12 hours

PHYSICAL PROPERTIES

- Maximum Application Temperature: 120°F
- Maximum Surface Temperature: 600°F (after cure)
- Count (per sq. in.) ± 10%: 18 x 14
- Weight (oz./sq. yd.) ± 10%: 14.8
- Thickness (in.) ± 10%: 0.024
- Breaking Strength (lb./in.):
 - Warp: 100
 - Fill: 45

CLEAN UP

Tools and drippings should be cleaned with warm soapy water before adhesive dries. Dispose of waste and contents/container in accordance with local/regional/national/international regulations.

PRECAUTIONS

Store in a dry, well-ventilated place at temperatures between 40°F (4.5°C) and 90°F (32°C). Store locked up. Keep container tightly closed. Approved respirators must be used to prevent inhalation of asbestos fibers that may be present in the air. Protective clothing should be worn. Dispose of contents/container in accordance with local/regional/national/international regulations.

Asbestos abatement activities must be performed in accordance with all applicable regulations including EPA, OSHA, Federal, State and Local. For more information always contact the appropriate agencies prior to beginning any abatement project.



*Professional Products
Professional Results*



INSULATION REPAIR LAGGING (5'x15' Blanket) Repair and/or Cover Asbestos Containing Insulation

- Water activated
- Withstands temperatures up to 600° F
- Top coated with Lag-Kote, Lag Kote II or SerpiMastic for complete encapsulation

NET CONTENTS: 5 Gallons

For Professional Use Only

Asbestos Abatement Products

CAUTION!
KEEP OUT OF REACH OF CHILDREN.

Do not take internally.
Close container after each use.
Keep from freezing.
Store between 40°F (4.5°C) and 90°F (32°C)
24 hour Emergency “CHEM-TEL” - 1-800-255-3924

**FIBERLOCK LAG KLOTH (PAILS) 6425
WARNING | ATTENTION**



H315 - Causes skin irritation.
H319 - Causes serious eye irritation.
H351 - Suspected of causing cancer.
H335 - May cause respiratory irritation.
H373 - May cause damage to organs through prolonged or repeated exposure.

H315 - Provoque une irritation cutanée.
H319 - Provoque une sévère irritation des yeux.
H351 - Susceptible de provoquer le cancer .
H335 - Peut irriter les voies respiratoires.
H373 - Risque présumé d'effets graves pour les organes à la suite d'expositions répétées ou d'une exposition prolongée.

Obtain special instructions before use.; Do not breathe dust/fume /gas/mist/vapours/spray.; Use only outdoors or in a well-ventilated area.; Use personal protective equipment as required.; Wear protective gloves/protective clothing/eye protection/face protection.; See SDS for full list of P phrases

Se procurer les instructions avant utilisation.|Porter des gants de protection/des vêtements de protection/un équipement de protection des yeux/du visage.|Utiliser l'équipement de protection individuel requis.|Éviter de respirer les brouillards/vapeurs/aérosols.|Éviter le rejet dans/l'environnement.|Les vêtements de travail contaminés ne devraient pas sortir du lieu de travail.|Voir SDS pour la liste complète des phrases P

IF exposed or concerned: Get medical advice/attention.; Specific treatment (see advice on this label).; Take off contaminated clothing and wash before reuse.; IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.; Call a POISON CENTER or doctor/physician if you feel unwell.; If eye irritation persists: Get medical advice/attention.; See SDS for full list of P phrases

EN CAS d'exposition prouvée ou suspectée: Consulter un médecin.|Traitement spécifique (voir les conseils sur cette étiquette).|Enlever les vêtements contaminés et les laver avant réutilisation|EN CAS DE CONTACT AVEC LES YEUX: rincer avec précaution à l'eau pendant plusieurs minutes. Enlever les lentilles de contact si la victime en porte et si elles peuvent être facilement enlevées. Continuer à rincer.|Appeler un CENTRE ANTIPOISON ou un médecin en cas de malaise.|Si l'irritation oculaire persiste: consulter un médecin.|Voir SDS pour la liste complète des phrases P

Canadian Contact Info:
4050-B Sladeview Crescent Suite 200
Mississauga, ON L5L 5Y5 Canada

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at www.fiberlock.com.

LAG KLOTH, the LAG KLOTH Logo and other marks on this label are trademarks of ICP Construction, Inc.

6425-U
5'x15'



150 Dascomb Rd.
Andover, MA 01810
(800) 342-3755
www.fiberlock.com
Rev. 10.16.18