



Professional Products
Professional Results



5000

Stain Blocking Primer

- Superior stain blocking
- Excellent adhesion to glossy surfaces

*Resists mold growth on the dry coating surface.

NET CONTENTS: 5 Gallons

For Professional Use Only

8350-5 White



150 Dascomb Rd.
Andover, MA 01810
(800) 342-3755
www.fiberlock.com
Rev. 10.16.18

IAQ 5000 is a white, quick drying, high performance 100% acrylic latex coating specifically designed to prime stained or water damaged surfaces. IAQ 5000 provides exceptional adhesion and stain blocking properties and may be used on interior or exterior surfaces to prevent most bleeding type stains, seal porous surfaces and provide adhesion to hard and glossy surfaces. IAQ 5000 also contains a fungistatic agent to resist mold growth on the dry coating surface. IAQ 5000 provides maximum breathability, adhesion, and holdout to prolong the life of the finish. IAQ 5000 is recommended for use on wallboard, plaster, sheetrock, masonry, wood, concrete, aluminum, and galvanized metal.

SURFACE PREPARATION

Warning! If you scrape, sand, or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH approved respirator to control lead exposure. Carefully clean up with a wet mop and HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD(5323) or log on to www.epa.gov/lead.

Surfaces to be coated must be free of dust, mildew, mold, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap and other surface contamination. Clean mold stained surfaces with IAQ Advanced Peroxide Cleaner, or use an EPA registered antimicrobial disinfectant cleaner such as IAQ 2000, IAQ 2500, ShockWave or ShockWave RTU.

Fill nicks, holes and voids with appropriate patching material and sand smooth prior to priming.

APPLICATION TOOLS

Apply IAQ 5000 with brush, roller or airless spray equipment.

- Brush: Synthetic, nylon or polyester bristle
- Roller: Synthetic fiber 3/8" nap or longer
- Spray: .015 to .023 tip @ 2200-2800 P.S.I.

PRODUCT APPLICATION

Material is supplied at application consistency but can be thinned sparingly with water if necessary to improve application characteristics. Thin with no more than 8oz. of water per gallon. Apply with appropriate application equipment. Some stains may require two coats of IAQ 5000; if an active stain discolors the primer, apply an additional coat to a small area to see if the stain is "locked" into the primer.

COVERAGE

- Smooth Surfaces: 400-500 ft²/gal.
- Porous Surfaces: 100-300 ft²/gal.

DRYING TIME @ 70°F 50% R.H

- To Touch: 30 minutes
- Recoat: 2 hours

CLEANUP

Clean tools and drippings with warm soapy water before IAQ 5000 dries. Dispose of waste according to all existing local, state and federal regulations.

PRECAUTIONS

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F. (32°C). Stir thoroughly. Do not mix with any other coatings, solvents or colors in oil. The IAQ 5000 coating is resistant to mold only on the surface of the coating. No mold resistance claim is made other than to the coating itself. Do not apply when air or surface temperature is below 50°F, or when drying conditions are poor or when surfaces are above a 15% moisture level content. Use adequate ventilation during application. When applying with a sprayer, wear a NIOSH approved respirator with any R, P, N or HE filter. For interior use only.

Calculated VOC: 93 g/l

FIBERLOCK IAQ 5000 8350
DANGER | DANGER



- H317 - May cause an allergic skin reaction.
- H351 - Suspected of causing cancer.
- H372 - Causes damage to organs through prolonged or repeated exposure.
- H411 - Toxic to aquatic life with long lasting effects.

Obtain special instructions before use.; Do not breathe dust/fume/gas/mist/vapours/spray.; Wear protective gloves/protective clothing/eye protection/face protection.; Use personal protective equipment as required.; Do not eat, drink or smoke when using this product.; Avoid release to the environment.; See SDS for full list of P phrases

IF exposed or concerned: Get medical advice/attention.; Specific treatment (see advice on this label); Wash contaminated clothing before reuse.; IF ON SKIN: Wash with plenty of soap and water.; Get medical advice/attention if you feel unwell.; If skin irritation or rash occurs: Get medical advice/attention.; See SDS for full list of P phrases

Canadian Contact Info:
4050-B Sladeview Crescent Suite 200
Mississauga, ON L5L 5Y5 Canada

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability of, for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at www.fiberlock.com.

IAQ, the IAQ Logo and other marks on this label are trademarks of ICP Construction, Inc.