

Scan this QR code with your smartphone for:

- Product Data Sheet and SDS
- Non-English Product Information
- Additional Product Information



IAQ 6000 is a white, tintable mold resistant coating for professional use, that contains a fungistatic agent to resist mold growth on the dry coating surface. IAQ 6000 is a durable, flexible, and permeable 100% acrylic water based coating. IAQ 6000 has been tested by independent and certified laboratories to prove resistance to mold growth on the surface of the coating, and has successfully passed both ASTM G-21 and ASTM D-3273 mold resistance testing with the highest scores possible. IAQ 6000 is recommended for use on wood, plaster, wallboard, sheetrock, concrete, masonry block, primed metal and galvanized metal. IAQ 6000 can also be used on new structural materials during building construction.

SURFACE PREPARATION

Surfaces to be coated must be free of dust, mildew, mold, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap and other surface contamination. Clean mold stained surfaces with IAQ Advanced Peroxide Cleaner, or use an EPA registered antimicrobial disinfectant cleaner such as IAQ 2000, IAQ 2500, ShockWave or ShockWave RTU.

Patch irregularities with vinyl patching paste or an appropriate patching compound. IAQ 6000 is self-priming over bare sheetrock, composition board, ceiling tile and concrete.

WALLBOARD, SHEETROCK, GYPSUM BOARD - Joint cement should be sanded smooth, but avoid abrading the paper.

FERROUS METAL - Clean, then prime with IAQ 4000 rust inhibiting direct-to-metal primer.

WOOD - Seal knots and stains with IAQ 5000 stain-blocking primer.

MASONRY BLOCK - Apply one coat of IAQ 3000 block filler if a denser surface is desired.

APPLICATION TOOLS

Apply IAQ 6000 with brush, roller or airless spray equipment.

- Brush: Synthetic, nylon or polyester bristle
- Roller: Synthetic fiber 3/8" nap or longer
- Spray: .019 to .021 tip @ 2000-3000 P.S.I.

TINTING

IAQ 6000 may be tinted to any off-white or pastel based color. Add up to 2 oz. of universal colorant per gallon. Start with 50% of the tinting formula and adjust as necessary.

PRODUCT APPLICATION

IAQ 6000 is supplied ready to use, but can be thinned sparingly with water (up to 1/2 pint water per gallon) for

proper application consistency if necessary. Apply IAQ 6000 generously and uniformly by brush, roller, or airless spray. Apply one coat of IAQ 6000 and ensure that the finished surface is properly sealed. To ensure that the finished surface is properly sealed, two-coats may be required on some porous surfaces.

COVERAGE

- Smooth Surfaces: 250-400 ft²/gal.
- Porous Surfaces: 150-300 ft²/gal.

DRYING TIME @ 70°F 50% R.H

- To Touch: 1 Hour
- Recoat: 4 Hours

CLEANUP

Clean tools and drippings with warm soapy water before IAQ 6000 dries. Dispose of waste according to all existing local, state and federal regulations.

PRECAUTIONS

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F. (32°C). Stir thoroughly. Do not mix with any other coatings, solvents or colors in oil. The IAQ 6000 coating is resistant to mold only on the surface of the coating. No mold resistance claim is made other than to the coating itself. The use of this product does not protect users or others against food-borne or disease-causing bacteria, viruses, germs or other disease-causing organisms. Do not apply when air or surface temperature is below 50°F, or when drying conditions are poor or when surfaces are above a 15% moisture level content. Use adequate ventilation during application. When applying with a sprayer, wear a NIOSH approved respirator with any R, P, N or HE filter. For interior use only.

WARNING! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Hazardous dust may be formed when sanded. Do not breathe dust. Use adequate ventilation.

VOC CONTENT

1.7 g/L (calculated as per EPA) / 6 g/L (calculated as per SCAQMD)

MADE IN USA WITH GLOBALLY SOURCED MATERIALS



Professional Products
Professional Results

IAQ 6000

SUPERIOR MOLD INHIBITION ON THE DRY COATING SURFACE

EXCEPTIONAL HIDE WITH TRUE ONE COAT COVERAGE

SUSTAINABLE ACTIVE INGREDIENT

ULTRA LOW VOC

*Resists mold growth on the dry coating surface

For Professional Use Only

MOLD RESISTANT COATING

.....

ULTRA LOW VOC MOLD RESISTANT COATING*

WHITE (TINTABLE)

24 HOUR EMERGENCY CHEMTEL - 1-800-255-3924

PRECAUTIONS

Do not handle until all safety precautions have been read and understood. **KEEP OUT OF REACH OF CHILDREN. FIRST AID:** If exposed or concerned, get medical advice/attention. **Contents:** Titanium dioxide, zinc oxide, aluminum oxide, pyrrhione zine, 2-amino-2-methylpropanol, and tetrapotassium pyrophosphate. **STORAGE:** Store locked up. **DISPOSAL:** Dispose of contents/container to an approved waste disposal plant. Keep from freezing. Store between 40-90F (4.5-32C).

FOR TECHNICAL INFORMATION CALL 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Building Solutions Group, nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at www.fiberlock.com.

WARNING! If you scrape, sand or remove old paint it may generate dust containing lead or titanium dioxide. Avoid inhaling dust. Wear a NIOSH-approved respirator to control exposure. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, EXPECIALLY IN CHILDREN. PREGNANT WOMENT SHOULD ALSO AVOID EXPOSURE. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800.424.LEAD or log on to www.epa.gov/lead

IAQ, the IAQ Logo and other marks on this label are trademarks of ICP Building Solutions Group.



FBC™ System Compatible indicates that this product has been tested, and is monitored on an ongoing basis, to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® piping systems and products made with TempRite® Technology.” “FBC™, FlowGuard Gold®, BlazeMaster® Corzan®, and TempRite® are trademarks of The Lubrizol Corporation or its affiliates.



WARNING: This product can expose you to chemicals including titanium dioxide (airborne, unbound particles of respirable size) a chemical known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

8360-5
White



NET CONTENTS:
5 GALLONS (18.93L)

150 Dascomb Rd.
Andover, MA 01810
(800) 342-3755
www.fiberlock.com
Rev. 03.9.22

