

Fiberlock IAQ 8000 Sealant White 8380

ICP Building Solutions Group (CAN)

Version No: **5.8**Safety Data Sheet according to WHMIS 2015 requirements

Issue Date: 02/03/2020 Print Date: 02/03/2020 S.GHS.CAN.EN

SECTION 1 IDENTIFICATION

Product Identifier

Product name	Fiberlock IAQ 8000 Sealant White 8380	
Synonyms	Not Available	
Other means of identification	Not Available	

Recommended use of the chemical and restrictions on use

Relevant identified uses Insulation Sealer

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Building Solutions Group (CAN)	
Address	55 Bay St. North Hamilton, Ontario L8L 1H1 Canada	
Telephone	8-623-9980	
Fax	Not Available	
Website	www.icpgroup.com	
Email	Not Available	

Emergency phone number

Association / Organisation	Chemtel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Eye Irritation Category 2A, Carcinogenicity Category 1B, Specific target organ toxicity - repeated exposure Category 2, Acute Aquatic Hazard Category 3, Skin Corrosion/Irritation Category 2, Skin Sensitizer Category 1, Germ cell mutagenicity Category 2, Chronic Aquatic Hazard Category 3

Label elements

Hazard pictogram(s)





SIGNAL WORD DANGE

Hazard statement(s

Hazard statement(s)	
H319	Causes serious eye irritation.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H315	Causes skin irritation.

Version No: 5.8 Page 2 of 16 Issue Date: 02/03/2020 Print Date: 02/03/2020

Fiberlock IAQ 8000 Sealant White 8380

H317	May cause an allergic skin reaction.
H341	Suspected of causing genetic defects.
H412	Harmful to aquatic life with long lasting effects.

Physical and Health hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.	
P260	Do not breathe mist/vapours/spray.	

Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/ attention.	
P321	Specific treatment (see advice on this label).	

Precautionary statement(s) Storage

P405 Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
57-55-6	1.14-1.2	propylene glycol
7631-86-9	not spec	silica amorphous
56709-13-8	0.2	azadioxabicyclooctane, isomer 1
7320-34-5	0.1	potassium pyrophosphate
1897-45-6	0.44	chlorothalonil
124-68-5	>0.81	monoisobutanolamine
27646-80-6	<0.06	2-(methylamino)-2-methyl-1-propanol
13463-67-7	6.42-10.7	titanium dioxide
1332-58-7	10.2	kaolin
64742-52-5	6.46	naphthenic distillate, heavy, hydrotreated (mild)
25265-77-4	>0.69	2.2.4-trimethyl-1.3-pentanediol monoisobutyrate
6846-50-0	<0.01	2,2,4-trimethyl-1,3-pentanediol diisobutyrate
Not Available	52.8	Non-hazardous ingredient
1314-13-2	1.13	zinc oxide

SECTION 4 FIRST-AID MEASURES

Description of first aid measures

Eye Contact If this product comes in contact with the eyes:	
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes, aerosols or combustion products are inhaled remove from contaminated area. Other measures are usually unnecessary.

Version No: **5.8** Page **3** of **16** Issue Date: **02/03/2020**

Fiberlock IAQ 8000 Sealant White 8380

Print Date: 02/03/2020

Ingestion

- ► Immediately give a glass of water.
- ▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIRE-FIGHTING MEASURES

Extinguishing media

- ► Foam.
- ► Dry chemical powder.

Special hazards arising from the substrate or mixture

Fire Incompatibility

▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Special protective equipment and precautions for fire-fighters

Fire Fighting

- ► Alert Fire Brigade and tell them location and nature of hazard.
- ▶ Wear full body protective clothing with breathing apparatus.

Fire/Explosion Hazard

Combustible.

▶ Slight fire hazard when exposed to heat or flame.

Combustion products include:

carbon dioxide (CO2)

other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	Environmental hazard - contain spillage. • Remove all ignition sources. • Clean up all spills immediately.	
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Environmental hazard - contain spillage. 	

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. DO NOT allow clothing wet with material to stay in contact with skin	
Other information	 ▶ Store in original containers. ▶ Keep containers securely sealed. 	

Conditions for safe storage, including any incompatibilities

Conditions for safe storage, in	cluding any incompatibilities
Suitable container	 Metal can or drum Packaging as recommended by manufacturer. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	Titanium dioxide reacts with strong acids, strong oxidisers reacts violently with aluminium, calcium, hydrazine, lithium (at around 200 deg C.), magnesium, potassium, sodium, zinc, especially at elevated temperatures - these reactions involves reduction of the oxide and are accompanied by incandescence dust or powders can ignite and then explode in a carbon dioxide atmosphere Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Version No: 5.8 Page 4 of 16 Issue Date: 02/03/2020 Print Date: 02/03/2020

Fiberlock IAQ 8000 Sealant White 8380

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

INGREDIENT DATA						
Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Ontario Occupational Exposure Limits	propylene glycol	1,2-Propylene glycol	50 ppm / 155; 10 mg/m3	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	silica amorphous	Silica Amorphous: Diatomaceous earth (uncalcined) (respirable fraction ++)	3 mg/m3	6 mg/m3	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	silica amorphous	Silica Amorphous: Silica, fume (respirable fraction++)	2 mg/m3	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	silica amorphous	Silica Amorphous: Silica, fused (respirable fraction++)	0.1 mg/m3	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	silica amorphous	Silica Amorphous: Diatomaceous earth (uncalcined) (inhalable fraction ++)	10 mg/m3	20 mg/m3	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	silica amorphous	Silica Amorphous: Precipitated silica and silica gel	10 mg/m3	20 mg/m3	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	silica amorphous	Silica - Amorphous, fused	0.1 mg/m3	Not Available	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	silica amorphous	Silica - Amorphous, Diatomaceous earth (uncalcined)	6 mg/m3	Not Available	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	silica amorphous	Silica - Amorphous, fumes	2 mg/m3	Not Available	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits (English)	silica amorphous	Silica Amorphous: Precipitated silica and silica gel	10 mg/m3	20 mg/m3	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits (English)	silica amorphous	Silica Amorphous: Diatomaceous earth (uncalcined) (inhalable fraction)	10 mg/m3	20 mg/m3	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits (English)	silica amorphous	Silica Amorphous: Diatomaceous earth (uncalcined) (respirable fraction)	3 mg/m3	6 mg/m3	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits (English)	silica amorphous	Silica, fused (respirable fraction)	0.1 mg/m3	Not Available	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	silica amorphous	Silica, Amorphous - Fume, Respirable	1.5 mg/m3	Not Available	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	silica amorphous	Silica, Amorphous - Diatomaceous earth (uncalcined) Total	4 mg/m3	Not Available	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	silica amorphous	Silica, Amorphous - Diatomaceous earth (uncalcined), Respirable	1.5 mg/m3	Not Available	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	silica amorphous	Silica, Amorphous - Precipitated and gel, Respirable	1.5 mg/m3	Not Available	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	silica amorphous	Silica, Amorphous - Precipitated and gel, Total	4 mg/m3	Not Available	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	silica amorphous	Silica, Amorphous - Fume Total	4 mg/m3	Not Available	Not Available	Not Available
Canada - Ontario Occupational Exposure Limits	silica amorphous	Silica fused	0.1 mg/m3	Not Available	Not Available	Not Available
Canada - Ontario Occupational Exposure Limits	silica amorphous	Silica fume	2 mg/m3	Not Available	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	titanium dioxide	Titanium dioxide	10 mg/m3	Not Available	Not Available	TLV Basis: lower respiratory tract irritation
Canada - Alberta Occupational Exposure Limits	titanium dioxide	Titanium dioxide	10 mg/m3	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination	titanium dioxide	Titanium dioxide	10 mg/m3	20 mg/m3	Not Available	Not Available

Version No: 5.8 Page **5** of **16** Issue Date: 02/03/2020 Print Date: 02/03/2020

Fiberlock IAQ 8000 Sealant White 8380

Limits	1		1		1	
Canada - Manitoba	titonium diavida	Not Available	10 ma/m2	Not	Not	TI V@ Pagin: I PT :
Occupational Exposure Limits	titanium dioxide	Not Available	10 mg/m3	Available	Available	TLV® Basis: LRT irr
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	titanium dioxide	Titanium dioxide	10 mg/m3	Not Available	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits (English)	titanium dioxide	Titanium dioxide	10 mg/m3	20 mg/m3	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	titanium dioxide	Titanium dioxide	10 mg/m3	Not Available	Not Available	(N) - the 8-hour TWA listed in the Table is for the total dust. The substance also has an 8-hour TWA of 3 mg/m 3 for the respirable fraction.
Canada - Prince Edward Island Occupational Exposure Limits	titanium dioxide	Titanium dioxide	10 mg/m3	Not Available	Not Available	TLV® Basis: LRT irr
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	kaolin	Kaolin	Not Available	Not Available	Not Available	(See Table 11)
Canada - Nova Scotia Occupational Exposure Limits	kaolin	Kaolin	2 mg/m3	Not Available	Not Available	TLV Basis: pneumoconiosis. Value is for particulate matter containing no asbestos and <1% crystalline silica.
Canada - Alberta Occupational Exposure Limits	kaolin	Kaolin respirable	2 mg/m3	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	kaolin	Kaolin (respirable fraction++)	2 mg/m3	4 mg/m3	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	kaolin	Not Available	2 mg/m3	Not Available	Not Available	TLV® Basis: Pneumoconiosis
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	kaolin	Kaolin	5 mg/m3	Not Available	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits (English)	kaolin	Kaolin (respirable fraction)	2 mg/m3	4 mg/m3	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	kaolin	Kaolin, Respirable	2 mg/m3	Not Available	Not Available	(E) - the value is for particulate matter containing no asbestos and less than 1% crystalline silica.
Canada - Prince Edward Island Occupational Exposure Limits	kaolin	Kaolin	2 mg/m3	Not Available	Not Available	TLV® Basis: Pneumoconiosis
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	naphthenic distillate, heavy, hydrotreated (mild)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	naphthenic distillate, heavy, hydrotreated (mild)	Oil mist - mineral	5 mg/m3	10 mg/m3	Not Available	TLV Basis: lung. As sampled by method that does not collect vapor.
Canada - Alberta Occupational Exposure Limits	naphthenic distillate, heavy, hydrotreated (mild)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	naphthenic distillate, heavy, hydrotreated (mild)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	naphthenic distillate, heavy, hydrotreated (mild)	Not Available	Not Available	Not Available	Not Available	TLV® Basis: URT irr
Canada - Manitoba Occupational Exposure Limits	naphthenic distillate, heavy, hydrotreated (mild)	Not Available	5 mg/m3	Not Available	Not Available	TLV® Basis: URT irr
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	naphthenic distillate, heavy, hydrotreated (mild)	Mineral oil (mist)	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits (English)	naphthenic distillate, heavy, hydrotreated (mild)	Oil mist, mineral	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	naphthenic distillate, heavy, hydrotreated (mild)	Oil mist - mineral, severely refined	1 mg/m3	Not Available	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	naphthenic distillate, heavy, hydrotreated (mild)	Oil mist - mineral, mildly refined	0.2 mg/m3	Not Available	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	naphthenic distillate, heavy, hydrotreated (mild)	Mineral oil, excluding metal working fluids - Pure, highly and severely refined	5 mg/m3	Not Available	Not Available	TLV® Basis: URT irr

Version No: 5.8 Page 6 of 16 Issue Date: 02/03/2020 Print Date: 02/03/2020

Fiberlock IAQ 8000 Sealant White 8380

Canada - Prince Edward Island Occupational Exposure Limits	naphthenic distillate, heavy, hydrotreated (mild)	Mineral oil, excluding metal working fluids - Poorly and mildly refined	Not Available	Not Available	Not Available	TLV® Basis: URT irr
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	zinc oxide	Zinc oxide fume	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	zinc oxide	Zinc oxide dust	Not Available	Not Available	Not Available	(See Table 11)
Canada - Nova Scotia Occupational Exposure Limits	zinc oxide	Zinc oxide	2 mg/m3	10 mg/m3	Not Available	TLV Basis: metal fume fever
Canada - Alberta Occupational Exposure Limits	zinc oxide	Zinc oxide, respirable	2 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	zinc oxide	Zinc oxide, fume and dust (respirable fraction++)	2 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	zinc oxide	Not Available	2 mg/m3	10 mg/m3	Not Available	TLV® Basis: Metal fume fever
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	zinc oxide	Zinc, oxide: Fume	5 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	zinc oxide	Zinc, oxide: Dust	10 mg/m3	Not Available	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants (English)	zinc oxide	Zinc, oxide	Not Available	Not Available	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits (English)	zinc oxide	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Inhalable fraction	10 mg/m3	20 mg/m3	Not Available	Not Available
Canada - Northwest Territories Occupational Exposure Limits (English)	zinc oxide	Particles (Insoluble or Poorly Soluble) Not Otherwise Specified: Respirable fraction	3 mg/m3	6 mg/m3	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	zinc oxide	Zinc oxide, Respirable	2 mg/m3	10 mg/m3	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	zinc oxide	Zinc oxide	2 mg/m3	10 mg/m3	Not Available	TLV® Basis: Metal fume fever
Canada - Ontario Occupational	zina avida	Particles (Insoluble or	10; 3	Not	Not	Not Available

| EMERGENCY LIMITS

Exposure Limits

zinc oxide

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
propylene glycol	Polypropylene glycols	30 mg/m3	330 mg/m3	2,000 mg/m3
propylene glycol	Propylene glycol; (1,2-Propanediol)	30 mg/m3	1,300 mg/m3	7,900 mg/m3
silica amorphous	Silica gel, amorphous synthetic	18 mg/m3	200 mg/m3	1,200 mg/m3
silica amorphous	Silica, amorphous fumed	18 mg/m3	100 mg/m3	630 mg/m3
silica amorphous	Siloxanes and silicones, dimethyl, reaction products with silica; (Hydrophobic silicon dioxide, amorphous)	120 mg/m3	1,300 mg/m3	7,900 mg/m3
silica amorphous	Silica, amorphous fume	45 mg/m3	500 mg/m3	3,000 mg/m3
silica amorphous	Silica amorphous hydrated	18 mg/m3	220 mg/m3	1,300 mg/m3
potassium pyrophosphate	Potassium pyrophosphate; (Tetrapotassium diphosphorate)	61 mg/m3	680 mg/m3	1,200 mg/m3
chlorothalonil	Chlorothalonil; (Tetrachloroisophthalonitrile)	0.13 mg/m3	1.4 mg/m3	8.6 mg/m3
monoisobutanolamine	Isobutanol-2-amine	17 mg/m3	190 mg/m3	570 mg/m3
titanium dioxide	Titanium oxide; (Titanium dioxide)	30 mg/m3	330 mg/m3	2,000 mg/m3
naphthenic distillate, heavy, hydrotreated (mild)	Distillates (petroleum) hydrotreated heavy naphthenic	140 mg/m3	1,500 mg/m3	8,900 mg/m3
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	Trimethyl-1,3-pentanediol monoisobutyrate, 2,2,4-; (Texanol)	13 mg/m3	140 mg/m3	840 mg/m3
zinc oxide	Zinc oxide	10 mg/m3	15 mg/m3	2,500 mg/m3

mg/m3

Poorly Soluble) Not Otherwise Specified (PNOS)

Available

Available

Not Available

Version No: **5.8** Page **7** of **16** Issue Date: **02/03/2020**

Fiberlock IAQ 8000 Sealant White 8380

Print Date: 02/03/2020

Ingredient	Original IDLH	Revised IDLH
propylene glycol	Not Available	Not Available
silica amorphous	3,000 mg/m3	Not Available
azadioxabicyclooctane, isomer 1	Not Available	Not Available
potassium pyrophosphate	Not Available	Not Available
chlorothalonil	Not Available	Not Available
monoisobutanolamine	Not Available	Not Available
2-(methylamino)-2-methyl- 1-propanol	Not Available	Not Available
titanium dioxide	5,000 mg/m3	Not Available
kaolin	Not Available	Not Available
naphthenic distillate, heavy, hydrotreated (mild)	2,500 mg/m3	Not Available
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	Not Available	Not Available
2,2,4-trimethyl-1,3-pentanediol diisobutyrate	Not Available	Not Available
Non-hazardous ingredient	Not Available	Not Available
zinc oxide	500 mg/m3	Not Available

OCCUPATIONAL EXPOSURE BANDING

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit		
azadioxabicyclooctane, isomer 1	E	≤ 0.01 mg/m³		
potassium pyrophosphate	Е	≤ 0.01 mg/m³		
chlorothalonil	E	≤ 0.01 mg/m³		
monoisobutanolamine	E	≤ 0.01 mg/m³		
2-(methylamino)-2-methyl- 1-propanol	E	≤ 0.01 mg/m³		
2,2,4-trimethyl-1,3-pentanediol diisobutyrate	E	≤ 0.1 ppm		
	Occupational exposure handing is a process of assigning chemicals into specific categories or hands based on a chemical's potency and the			

Exposure controls

Notes:

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a

Personal protection







range of exposure concentrations that are expected to protect worker health.



Eye and face protection

- ► Safety glasses with side shields.
- Chemical goggles.

Skin protection

See Hand protection below

- ► Wear chemical protective gloves, e.g. PVC.
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber

NOTE:

Hands/feet protection

► The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Body protection

See Other protection below

Other protection

- Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent]
- Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges.
- Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels.
- Overalls.
- ▶ P.V.C.

Respiratory protection

 Version No: 5.8
 Page 8 of 16
 Issue Date: 02/03/2020

Fiberlock IAQ 8000 Sealant White 8380

Print Date: 02/03/2020

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	8.5	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.
Ingestion	Ingestion of propylene glycol produced reversible central nervous system depression in humans following ingestion of 60 ml. Symptoms included increased heart-rate (tachycardia), excessive sweating (diaphoresis) and grand mal seizures in a 15 month child who ingested large doses (7.5 ml/day for 8 days) as an ingredient of vitamin preparation. The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. The liquid may be able to be mixed with fats or oils and may degrease the skin, producing a skin reaction described as non-allergic contact dermatitis. The material is unlikely to produce an irritant dermatitis as described in EC Directives.
Eye	This material can cause eye irritation and damage in some persons.
Chronic	Strong evidence exists that this substance may cause irreversible mutations (though not lethal) even following a single exposure. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.

Version No: 5.8 Page 9 of 16 Issue Date: 02/03/2020

Fiberlock IAQ 8000 Sealant White 8380

Print Date: 02/03/2020

There is ample evidence that this material can be regarded as being able to cause cancer in humans based on experiments and other information.

Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.

This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.

Chronic dust inhalation of kaolin, can cause kaolinosis from kaolin deposition in the lungs causing distinct lung markings, abnormal inflation of air sacs, and chronic lung diseases (nodular pneumoconiosis). This condition is made worse by long duration of occupational exposure and pre-existing chest infection. Pre-employment screening is recommended.

Repeated application of mildly hydrotreated oils (principally paraffinic), to mouse skin, induced skin tumours; no tumours were induced with

severely hydrotreated oils.

Propylene glycol is thought to be sensitizing following the regular use of topical creams by eczema patients. Testing in humans showed that 16% of exposed individuals, irritation occurred, with 12.5% showing toxic or allergic reactions.

berlock IAQ 8000 Sealant	TOXICITY	IRRITATION
White 8380	Not Available	Not Available
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 11890 mg/kg ^[2]	Eye (rabbit): 100 mg - mild
	Inhalation (rat) LC50: >44.9 mg/l/4H ^[2]	Eye (rabbit): 500 mg/24h - mild
propylene glycol	Oral (rat) LD50: 20000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
		Skin(human):104 mg/3d Intermit Mod
		Skin(human):500 mg/7days mild
		Skin: no adverse effect observed (not irritating) ^[1]
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >5000 mg/kg ^[2]	Eye (rabbit): non-irritating *
silica amorphous	Inhalation (rat) LC50: >0.139 mg/l/14h**[Grace] ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
	Oral (rat) LD50: 3160 mg/kg ^[2]	Skin (rabbit): non-irritating *
		Skin: no adverse effect observed (not irritating) ^[1]
	TOXICITY	IRRITATION
azadioxabicyclooctane, isomer 1	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Not Available
isomer i	Oral (rat) LD50: 2950 mg/kg ^[2]	
	TOXICITY	IRRITATION
otassium pyrophosphate	dermal (rat) LD50: >2000 mg/kg ^[1]	Eye: adverse effect observed (irritating) ^[1]
	Oral (rat) LD50: >300-2000 mg/kg ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
	TOXICITY	IRRITATION
	dermal (rat) LD50: >2500 mg/kg ^[2]	Not Available
chlorothalonil	Inhalation (rat) LC50: 0.0775 mg/l/1h[2]	
	Oral (rat) LD50: >5000 mg/kg ^[2]	
	TOXICITY	IRRITATION
monoisobutanolamine	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Not Available
	Oral (rat) LD50: 2900 mg/kg ^[2]	
-(methylamino)-2-methyl-	TOXICITY	IRRITATION
1-propanol	Not Available	Not Available
	TOXICITY	IRRITATION
	dermal (hamster) LD50: >=10000 mg/kg[2]	Eye: no adverse effect observed (not irritating) ^[1]
titanium dioxide	Oral (rat) LD50: >2000 mg/kg ^[1]	Skin (human): 0.3 mg /3D (int)-mild *
		Skin: no adverse effect observed (not irritating) ^[1]
1 !!	TOXICITY	IRRITATION
kaolin	Not Available	Not Available
	TOXICITY	IRRITATION
ohthenic distillate, heavy,	Dermal (rabbit) LD50: >2000 mg/kg ^[2]	Eye: no adverse effect observed (not irritating) ^[1]
hydrotreated (mild)	Inhalation (rat) LC50: >5.3 mg/l4 h ^[1]	Skin: no adverse effect observed (not irritating) ^[1]
	Oral (rat) LD50: >5000 mg/kg ^[2]	

Version No: 5.8 Page 10 of 16 Issue Date: 02/03/2020 Print Date: 02/03/2020

Fiberlock IAQ 8000 Sealant White 8380

TOXICITY IRRITATION Eye: no adverse effect observed (not irritating) $^{[1]}$ Dermal (rabbit) LD50: >15200 mg/kg^[2] Inhalation (rat) LC50: >5.325 mg/l/6h[2] Eves - Moderate irritant * 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate Skin - Slight irritant * Oral (rat) LD50: 3200 mg/kg[2] Skin (rabbit): mild *** Skin: no adverse effect observed (not irritating)^[1] TOXICITY IRRITATION Dermal (rabbit) LD50: >2000 mg/kg^[1] Eye (rabbit): very slight** 2,2,4-trimethyl-1,3-pentanediol Inhalation (rat) LC50: >7.95 mg/l/6h***[2] Eye: no adverse effect observed (not irritating)^[1] diisobutyrate Skin (guinea pig): 5000mg/kg-mild Oral (rat) LD50: >2000 mg/kg^[1] Skin: no adverse effect observed (not irritating)^[1] TOXICITY IRRITATION Non-hazardous ingredient Not Available Not Available TOXICITY IRRITATION dermal (rat) LD50: >2000 mg/kg[1] Eye (rabbit): 500 mg/24 h - mild Inhalation (rat) LC50: >1.79 mg/l4 h[1] Eye: no adverse effect observed (not irritating)^[1] zinc oxide Skin (rabbit): 500 mg/24 h- mild Oral (rat) LD50: >5000 mg/kg[2] Skin: no adverse effect observed (not irritating)^[1] 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise Legend: specified data extracted from RTECS - Register of Toxic Effect of chemical Substances Reports indicate high/prolonged exposures to amorphous silicas induced lung fibrosis in experimental animals; in some experiments these effects were reversible. [PATTYS] For silica amorphous: When experimental animals inhale synthetic amorphous silica (SAS) dust, it dissolves in the lung fluid and is rapidly eliminated. If swallowed, the SILICA AMORPHOUS vast majority of SAS is excreted in the faeces and there is little accumulation in the body. The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans Evidence of carcinogenicity may be inadequate or limited in animal testing. For azadioxabicyclooctanes: AZADIOXABICYCLOOCTANE, The acute oral and dermal toxicities of azadioxabicyclooctane are low. The acute inhalation toxicity showed a median lethal dose range of ISOMER 1 between 0.441 mg/L and 0.819 mg/L in males, and between 0.819 mg/L and 1.397 mg/L in females, with epistaxis, labored breathing, rales, and rhinorrhoea in all dose groups. * CCInfo **POTASSIUM** No data available. Data for sodium analogue only, tetrasodium pyrophosphate **PYROPHOSPHATE** CHLOROTHALONIL Chlorothalonil has low toxicity, according to animal testing. It irritates the skin and eye. ADI: 0.01 mg/kg/day NOEL: 1.5 mg/kg/day TRIS AMINO and its surrogate chemicals have very little, if any, toxicity. They are mildly irritating to eyes at moderate concentrations, and do not MONOISOBUTANOL AMINE cause allergic skin reactions. UCLID Exposure to titanium dioxide is via inhalation, swallowing or skin contact. When inhaled, it may deposit in lung tissue and lymph nodes causing TITANIUM DIOXIDE dysfunction of the lungs and immune system. Absorption by the stomach and intestines depends on the size of the particle The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. For bentonite clays: KAOLIN Bentonite (CAS No. 1302-78-9) consists of a group of clays formed by crystallization of vitreous volcanic ashes that were deposited in water. The expected acute oral toxicity of bentonite in humans is very low. The materials included in the Lubricating Base Oils category are related from both process and physical-chemical perspectives; The potential toxicity of a specific distillate base oil is inversely related to the severity or extent of processing the oil has undergone, since: The adverse effects of these materials are associated with undesirable components, and The levels of the undesirable components are inversely related to the degree of processing; Distillate base oils receiving the same degree or extent of processing will have similar toxicities; The potential toxicity of residual base oils is independent of the degree of processing the oil receives. The reproductive and developmental toxicity of the distillate base oils is inversely related to the degree of processing. Unrefined & mildly refined distillate base oils contain the highest levels of undesirable components, have the largest variation of hydrocarbon molecules and have shown the highest potential cancer-causing and mutation-causing activities. Highly and severely refined distillate base oils are produced from unrefined and mildly refined oils by removing or transforming undesirable components. NAPHTHENIC DISTILLATE, For unrefined and mildly refined distillate base oils Acute toxicity: Animal testing showed high semilethal doses of >5000 mg/kg body weight and >2 g/kg body weight for exposure by swallowing or HEAVY, HYDROTREATED (MILD) skin contact, respectively. The same material was also reported to be moderately irritating to skin, while not being sensitizing. Repeat dose toxicity: Animal testing showed that repeat dose toxicity was mild to moderate to the skin. Reproductive / developmental toxicity: No studies on developmental toxicity or reproduction are available Animal studies indicate that normal, branched and cyclic paraffins are absorbed from the gastrointestinal tract and that the absorption of n-paraffins is inversely proportional to the carbon chain length, with little absorption above C30. With respect to the carbon chain lengths likely to be present in mineral oil, n-paraffins may be absorbed to a greater extent than iso- or cyclo-paraffins.

The major classes of hydrocarbons are well absorbed into the gastrointestinal tract in various species.

production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.

The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the

Version No: 5.8 Page 11 of 16 Issue Date: 02/03/2020

Fiberlock IAQ 8000 Sealant White 8380

Print Date: 02/03/2020

	WARNING: This substance has been classified by the	IARC as Group 1: CARCINOGENIC	TO HUMANS.		
2,2,4-TRIMETHYL- 1,3-PENTANEDIOL MONOISOBUTYRATE	Not a skin sensitiser (guinea pig, Magnusson-Kligman) *** Ames Test: negative *** Micronucleus, mouse: negative *** Not mutagenic *** No effects on fertility or foetal development seen in the rat *** * [SWIFT] ** [Eastman] *** [Perstop] The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.				
2,2,4-TRIMETHYL- 1,3-PENTANEDIOL DIISOBUTYRATE	For 2,2,4-trimethyl-1,3-pentanediol diisobutyrate (TXIB) Laboratory testing showed that TXIB does not cause genetic toxicity. It may damage the kidneys of developing animals but only at levels that also affect the adult. NOAEL oral (rat), 103 days = 1% in diet *** NOEL oral (dog), 90 days = 1% in diet *** Mutagenicity/Genotoxicity Data: *** Chromosomal aberration assay: Negative (+/- activation) CHO/HGPRT assay: Negative (+/- activation) Salmonella-E.coli reverse mutation assay (Ames test): Negative (+/- activation) *,**,*** Various suppliers MSDS				
Fiberlock IAQ 8000 Sealant White 8380 & TITANIUM DIOXIDE	Laboratory (in vitro) and animal studies show, exposur producing mutation.	re to the material may result in a poss	ible risk of irreversible effects, with the possibility of		
Fiberlock IAQ 8000 Sealant White 8380 & AZADIOXABICYCLOOCTANE, ISOMER 1 & CHLOROTHALONIL	The following information refers to contact allergens a Contact allergies quickly manifest themselves as conteczema involves a cell-mediated (T lymphocytes) imm	act eczema, more rarely as urticaria c	·		
Fiberlock IAQ 8000 Sealant White 8380 & PROPYLENE GLYCOL	The acute oral toxicity of propylene glycol is very low; large amounts are needed to cause perceptible health damage in humans. Serious toxicity generally occurs only at blood concentrations over 1 g/L, which requires extremely high intake over a relatively short period of time; this is nearly impossible with consuming foods or supplements which contain 1g/kg of PG at most.				
PROPYLENE GLYCOL & TITANIUM DIOXIDE & 2,2,4- TRIMETHYL- 1,3-PENTANEDIOL MONOISOBUTYRATE & 2,2,4- TRIMETHYL- 1,3-PENTANEDIOL DIISOBUTYRATE & ZINC OXIDE	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.				
AZADIOXABICYCLOOCTANE, ISOMER 1 & POTASSIUM PYROPHOSPHATE & CHLOROTHALONIL & TITANIUM DIOXIDE	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound.				
CHLOROTHALONIL & TITANIUM DIOXIDE	WARNING: This substance has been classified by the	IARC as Group 2B: Possibly Carcino	ogenic to Humans.		
2-(METHYLAMINO)- 2-METHYL-1-PROPANOL & TITANIUM DIOXIDE & KAOLIN & NAPHTHENIC DISTILLATE, HEAVY, HYDROTREATED (MILD)	No significant acute toxicological data identified in liter	ature search.			
Acute Toxicity	×	Carcinogenicity	✓		
Skin Irritation/Corrosion	~	Reproductivity	×		
Serious Eye Damage/Irritation	*	STOT - Single Exposure	×		
Respiratory or Skin sensitisation	•	STOT - Repeated Exposure	•		
Mutagenicity	✓	Aspiration Hazard	×		

Legend:

X − Data either not available or does not fill the criteria for classification
 ✓ − Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

1					
Fiberlock IAQ 8000 Sealant White 8380	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>10-mg/L	2
propylene glycol	EC50	48	Crustacea	43-500mg/L	2
	EC50	96	Algae or other aquatic plants	19-mg/L	2
	NOEC	168	Fish	11-530mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
silica amorphous	LC50	96	Fish	1-289.09mg/L	2
	EC50	48	Crustacea	ca.7600mg/L	1
	EC50	72	Algae or other aquatic plants	440mg/L	1
	NOEC	720	Crustacea	34.223mg/L	2

Page 12 of 16

Issue Date: 02/03/2020 Print Date: 02/03/2020 Fiberlock IAQ 8000 Sealant White 8380 ENDPOINT TEST DURATION (HR) **SPECIES** VALUE SOURCE LC50 96 Fish 28073.682mg/L 3 azadioxabicyclooctane, EC50 96 Algae or other aquatic plants 503.941mg/L 3 isomer 1 LC50 96 Fish 7479.033mg/L 3 EC50 96 Algae or other aquatic plants 193.440mg/L 3 **ENDPOINT** TEST DURATION (HR) SPECIES VALUE SOURCE LC50 96 Fish >100mg/L 2 48 2 EC50 Crustacea >100mg/L potassium pyrophosphate EC50 72 Algae or other aquatic plants >100mg/L 2 NOEC 72 Algae or other aquatic plants >100mg/L 2 SPECIES SOURCE **ENDPOINT TEST DURATION (HR)** VALUE LC50 0.0076mg/L 0.0066475mg/L 48 EC50 Crustacea 4 chlorothalonil EC50 72 Algae or other aquatic plants 0.0068mg/L 4 BCF Algae or other aquatic plants 0.02mg/L 4 336 240 0.0003mg/L 4 NOEC Crustacea **ENDPOINT SPECIES** SOURCE **TEST DURATION (HR)** VALUE LC50 Fish =100mg/L 48 monoisobutanolamine EC50 Crustacea =193mg/L EC50 96 Algae or other aquatic plants 52.872mg/L 3 NOEC 48 2 Crustacea 100mg/L ENDPOINT **TEST DURATION (HR) SPECIES** VALUE SOURCE 2-(methylamino)-2-methyl-Not Not Not 1-propanol Not Available Not Available Available Available Available **ENDPOINT** TEST DURATION (HR) **SPECIES** VALUE SOURCE Fish 2 LC50 96 >1-mg/L titanium dioxide EC50 48 Crustacea >1-mg/L 2 EC50 72 5.83mg/L 4 Algae or other aquatic plants NOEC 336 Fish 0.089mg/L 4 **ENDPOINT** TEST DURATION (HR) SPECIES VALUE SOURCE kaolin Not Not Not Available Not Available Available Available Available **ENDPOINT TEST DURATION (HR)** SPECIES VALUE SOURCE LC50 96 Fish >100mg/L 2 naphthenic distillate, heavy, EC50 48 Crustacea >10-mg/L hydrotreated (mild) FC50 96 Algae or other aquatic plants >1000mg/L 1 504 NOEC Crustacea >1mg/L 1 **ENDPOINT TEST DURATION (HR) SPECIES** VALUE SOURCE LC50 9.552mg/L 3 2,2,4-trimethyl-1,3-pentanediol 48 2 EC50 Crustacea >19mg/L monoisobutyrate EC50 96 Algae or other aquatic plants 0.789mg/L 3 72 Algae or other aquatic plants 2 NOFC 2mg/L **ENDPOINT TEST DURATION (HR) SPECIES** VALUE SOURCE LC50 96 Fish 1.203mg/L 3 2,2,4-trimethyl-1,3-pentanediol

48

96

504

96

TEST DURATION (HR)

TEST DURATION (HR)

Not Available

EC50

EC50

NOEC

Not

LC50

ENDPOINT

Available

ENDPOINT

diisobutyrate

zinc oxide

Non-hazardous ingredient

2

3

2

Not

2

SOURCE

Available

SOURCE

>1.46mg/L

0.107ma/L

VALUE

Available

Not

0.001-0.58mg/L

VALUE

0.7mg/L

Algae or other aquatic plants

Crustacea

SPECIES

SPECIES

Fish

Not Available

Version No: 5.8 Page 13 of 16 Issue Date: 02/03/2020

Fiberle

lock IAQ 8000 Sealant White 8380	Print Date: 02/03/2020

EC50	48	Crustacea	0.001-0.014mg/L	2
EC50	72	Algae or other aquatic plants	0.037mg/L	2
BCF	336	Fish	4376.673mg/L	4
NOEC	72	Algae or other aquatic plants	0.00008138mg/L	2

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Bentonite and kaolin have low toxicity to aquatic species, a large number of which have been tested

Propylene glycol is known to exert high levels of biochemical oxygen demand (BOD) during degradation in surface waters. This process can adversely affect aquatic life by consuming oxygen needed by aquatic organisms for survival.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
propylene glycol	LOW	LOW
silica amorphous	LOW	LOW
azadioxabicyclooctane, isomer 1	HIGH	HIGH
chlorothalonil	HIGH	HIGH
monoisobutanolamine	LOW	LOW
titanium dioxide	HIGH	HIGH
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	LOW	LOW
2,2,4-trimethyl-1,3-pentanediol diisobutyrate	нівн	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation		
propylene glycol	OW (BCF = 1)		
silica amorphous	OW (LogKOW = 0.5294)		
azadioxabicyclooctane, isomer 1	OW (LogKOW = -1.5532)		
chlorothalonil	DW (BCF = 125)		
monoisobutanolamine	LOW (BCF = 330)		
titanium dioxide	LOW (BCF = 10)		
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	LOW (LogKOW = 2.9966)		
2,2,4-trimethyl-1,3-pentanediol diisobutyrate	LOW (BCF = 1)		
zinc oxide	LOW (BCF = 217)		

Mobility in soil

Ingredient	Mobility		
propylene glycol	IIGH (KOC = 1)		
silica amorphous	LOW (KOC = 23.74)		
azadioxabicyclooctane, isomer 1	LOW (KOC = 10)		
chlorothalonil	OW (KOC = 2392)		
monoisobutanolamine	MEDIUM (KOC = 2.196)		
titanium dioxide	LOW (KOC = 23.74)		
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	LOW (KOC = 22.28)		
2,2,4-trimethyl-1,3-pentanediol diisobutyrate	LOW (KOC = 607.5)		

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

- ▶ Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- ▶ It may be necessary to collect all wash water for treatment before disposal.

Version No: 5.8 Page 14 of 16 Issue Date: 02/03/2020

Fiberlock IAQ 8000 Sealant White 8380

Print Date: 02/03/2020

- Recycle wherever possible or consult manufacturer for recycling options.
- Consult State Land Waste Authority for disposal.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant

NO

Land transport (TDG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled **Products Regulations**

PROPYLENE GLYCOL IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada - Ontario Occupational Exposure Limits

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information

System - WHMIS GHS (English)

GESAMP/EHS Composite List - GESAMP Hazard Profiles

IMO IBC Code Chapter 17: Summary of minimum requirements

IMO IBC Code Chapter 18: List of products to which the Code does not apply

IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk

IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances

IMO Provisional Categorization of Liquid Substances - List 3: (Trade-named) mixtures containing at least 99% by weight of components already assessed by IMO, presenting safety hazards

SILICA AMORPHOUS IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada - British Columbia Occupational Exposure Limits

Canada - Northwest Territories Occupational Exposure Limits

Canada - Ontario Occupational Exposure Limits

Canada - Quebec Permissible Exposure Values for Airborne Contaminants

Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination

Limits

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Non-Domestic Substances List (NDSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS (English)

GESAMP/EHS Composite List - GESAMP Hazard Profiles

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

AZADIOXABICYCLOOCTANE. ISOMER 1 IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Transport Dangerous Goods - Schedule 1

Canada Transport Dangerous Goods - Schedule 3

International Air Transport Association (IATA) Dangerous Goods Regulations

International Maritime Dangerous Goods Requirements (IMDG Code)

United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

POTASSIUM PYROPHOSPHATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information

System - WHMIS GHS (English)

Canada Transport Dangerous Goods - Schedule 1

Canada Transport Dangerous Goods - Schedule 3

GESAMP/EHS Composite List - GESAMP Hazard Profiles

International Air Transport Association (IATA) Dangerous Goods Regulations

International Maritime Dangerous Goods Requirements (IMDG Code)

United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

CHLOROTHALONIL IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada - Saskatchewan Occupational Health and Safety Regulations - Designated

Chemical Substances

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Transport Dangerous Goods - Schedule 1

Canada Transport Dangerous Goods - Schedule 3

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC

Monographs - Group 2B: Possibly carcinogenic to humans

International Air Transport Association (IATA) Dangerous Goods Regulations

International Maritime Dangerous Goods Requirements (IMDG Code)

United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

MONOISOBUTANOLAMINE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information

System - WHMIS GHS (English)

GESAMP/EHS Composite List - GESAMP Hazard Profiles

IMO IBC Code Chapter 17: Summary of minimum requirements

IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk

2-(METHYLAMINO)-2-METHYL-1-PROPANOL IS FOUND ON THE FOLLOWING REGULATORY LISTS

TITANIUM DIOXIDE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Version No: 5.8 Page 15 of 16 Issue Date: 02/03/2020

Fiberlock IAQ 8000 Sealant White 8380

Print Date: 02/03/2020

Canada - Alberta Occupational Exposure Limits

Canada - British Columbia Occupational Exposure Limits

Canada - Manitoba Occupational Exposure Limits

Canada - Northwest Territories Occupational Exposure Limits

Canada - Nova Scotia Occupational Exposure Limits

Canada - Prince Edward Island Occupational Exposure Limits

Canada - Quebec Permissible Exposure Values for Airborne Contaminants

Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Non-Domestic Substances List (NDSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information

System - WHMIS GHS (English)

Chemical Footprint Project - Chemicals of High Concern List

GESAMP/EHS Composite List - GESAMP Hazard Profiles

IMO IBC Code Chapter 17: Summary of minimum requirements

IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

KAOLIN IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada - Alberta Occupational Exposure Limits

Canada - British Columbia Occupational Exposure Limits

Canada - Manitoba Occupational Exposure Limits

Canada - Northwest Territories Occupational Exposure Limits

Canada - Nova Scotia Occupational Exposure Limits

Canada - Prince Edward Island Occupational Exposure Limits

Canada - Quebec Permissible Exposure Values for Airborne Contaminants

Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination

Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information

System - WHMIS GHS (English)

Chemical Footprint Project - Chemicals of High Concern List

GESAMP/EHS Composite List - GESAMP Hazard Profiles

IMO IBC Code Chapter 18: List of products to which the Code does not apply International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

NAPHTHENIC DISTILLATE, HEAVY, HYDROTREATED (MILD) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada - Alberta Occupational Exposure Limits

Canada - British Columbia Occupational Exposure Limits

Canada - Manitoba Occupational Exposure Limits

Canada - Northwest Territories Occupational Exposure Limits

Canada - Nova Scotia Occupational Exposure Limits

Canada - Prince Edward Island Occupational Exposure Limits

Canada - Prince Edward Island Occupational Exposure Limits - Carcinogens

Canada - Quebec Permissible Exposure Values for Airborne Contaminants

Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination

Canada - Saskatchewan Occupational Health and Safety Regulations - Designated Chemical Substances

Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Chemical Footprint Project - Chemicals of High Concern List

IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1: Carcinogenic to humans

International FOSFA List of Banned Immediate Previous Cargoes

2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYRATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information

System - WHMIS GHS (English)

GESAMP/EHS Composite List - GESAMP Hazard Profiles

IMO IBC Code Chapter 17: Summary of minimum requirements

IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk

IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk

2,2,4-TRIMETHYL-1,3-PENTANEDIOL DIISOBUTYRATE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

GESAMP/EHS Composite List - GESAMP Hazard Profiles

IMO IBC Code Chapter 17: Summary of minimum requirements

NON-HAZARDOUS INGREDIENT IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

ZINC OXIDE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Canada - Alberta Occupational Exposure Limits

Canada - British Columbia Occupational Exposure Limits Canada - Manitoba Occupational Exposure Limits

Canada - Northwest Territories Occupational Exposure Limits

Canada - Nova Scotia Occupational Exposure Limits

Canada - Ontario Occupational Exposure Limits

Canada - Prince Edward Island Occupational Exposure Limits

Canada - Quebec Permissible Exposure Values for Airborne Contaminants

Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Non-Domestic Substances List (NDSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information

System - WHMIS GHS (English)

Canada Transport Dangerous Goods - Schedule 1

Canada Transport Dangerous Goods - Schedule 3

International Air Transport Association (IATA) Dangerous Goods Regulations

International Maritime Dangerous Goods Requirements (IMDG Code) United Nations Recommendations on the Transport of Dangerous Goods Model

Regulations

National Inventory Status

National Inventory	Status		
Australia - AICS	No (2-(methylamino)-2-methyl-1-propanol)		
Canada - DSL	No (2-(methylamino)-2-methyl-1-propanol)		
Canada - NDSL	No (chlorothalonil; monoisobutanolamine; kaolin; propylene glycol; naphthenic distillate, heavy, hydrotreated (mild); 2-(methylamino)-2-methyl-1-propanol; 2,2,4-trimethyl-1,3-pentanediol diisobutyrate; potassium pyrophosphate; 2,2,4-trimethyl-1,3-pentanediol monoisobutyrate; azadioxabicyclooctane, isomer 1)		
China - IECSC	Yes		
Europe - EINEC / ELINCS / NLP	No (2-(methylamino)-2-methyl-1-propanol)		

Version No: **5.8** Page **16** of **16** Issue Date: **02/03/2020**

Fiberlock IAQ 8000 Sealant White 8380

Print Date: 02/03/2020

Japan - ENCS	No (kaolin; potassium pyrophosphate; azadioxabicyclooctane, isomer 1)		
Korea - KECI	No (2-(methylamino)-2-methyl-1-propanol)		
New Zealand - NZIoC	Yes		
Philippines - PICCS	Yes		
USA - TSCA	No (2-(methylamino)-2-methyl-1-propanol)		
Taiwan - TCSI	Yes		
Mexico - INSQ	No (2-(methylamino)-2-methyl-1-propanol; potassium pyrophosphate)		
Vietnam - NCI	Yes		
Russia - ARIPS	No (chlorothalonil; 2-(methylamino)-2-methyl-1-propanol)		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)		

SECTION 16 OTHER INFORMATION

Revision Date	02/03/2020
Initial Date	08/17/2017

CONTACT POINT

SDS Version Summary

Version Is	Issue Date	Sections Updated
4.8.1.1.1	02/03/2020	Acute Health (eye), Acute Health (skin), Acute Health (swallowed), Chronic Health, Classification, Disposal, Environmental, Exposure Standard, Fire Fighter (extinguishing media), Fire Fighter (fire/explosion hazard), Fire Fighter (fire fighting), Fire Fighter (fire incompatibility), First Aid (eye), Handling Procedure, Ingredients, Personal Protection (Respirator), Spills (minor), Storage (storage incompatibility), Storage (storage requirement), Storage (suitable container)

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings.

Definitions and abbreviations

 ${\sf PC-TWA} : {\sf Permissible\ Concentration-Time\ Weighted\ Average}$

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors

BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.

^{**}PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES**