

Grip-Tack

Lockdown & Adhesive For Lead & Asbestos

Product Description

6408-Clear

Grip-Tack is a high solids, water based multipurpose lockdown/adhesive for capturing and sealing residual contaminants present before, during, and after demolition or removal projects. Its unique formulation provides a soft, tacky, flexible membrane, which locks down asbestos fibers, lead paint chips and dust to insure final clearance after the removal of lead and/or asbestos. The sticky finish traps lead dust and airborne fibers making it ideal for over-coating lead paint or asbestos prior to their removal or demolition. This product is also suitable for use as a lead paint adhesive primer for use over high gloss surfaces containing lead paint.

Application Information

LEAD APPLICATION INFORMATION

Consult all related local, state and federal regulations regarding work practices and personal protection to be used prior to surface preparation, including OSHA's Lead Exposure in Construction Standard, Title 29 of the Code of Federal Regulations, Part 1926, Section 62 (29 CFR 1926.62).

PRIMER COAT FOR EVENTUAL ENCAPSULATION OF LEAD-BASED PAINT: Inspect all surfaces to be treated to insure they are clean, dry and free of all foreign matter including: dust, rust, grease, oil, mildew, glue size, calcimine, wax, soap, loose paint, etc. Patch and repair irregularities in surfaces with an appropriate patching compound. Allow to dry and wet sand smooth. Using a brush, roller or airless sprayer; apply Grip-Tack at a rate of approximately 200 sq.ft. per gallon. Grip-Tack should be coated with L-B-C Lead Barrier Compound one hour after application.

DEMOLITION ADHESIVE: Structural components previously painted with lead-based paint should be over-coated with Grip-Tack prior to their removal. Grip-Tack's outstanding adhesion and soft tacky finish traps lead dust and minimizes lead paint chip contamination. Grip-Tack should be spray applied at a rate of 100 to 200 sq.ft. per gallon over the entire component system.

LOCKDOWN: Grip-Tack will bind residual lead paint chips and dust for final dust wipe clearance, and provide a primed surface which can be top-coated with a 100% acrylic latex paint.

ASBESTOS APPLICATION INFORMATION

Approved respirators must be used to prevent the inhalation of asbestos fibers that may be present in the air. Careful consideration should be given to all EPA, OSHA, and State regulations in effect at the time of application. The EPA, through the Office of Pesticides and Toxic Substances, has issued a report headed "Guidance for Controlling Friable Asbestos Containing Materials in Buildings", EPA 560/5 85-024 June 1985, containing the proper data, cautions and procedures for asbestos control. Copies are available from: TSCA Industry Asst. Office, EPA TS-799, 401 M Street SW, Washington, DC 20460, (202) 554-1404.

DEMOLITION ADHESIVE: Apply Grip-Tack to all surfaces prior to demolition or component disassembly. Grip-Tack's adhesive membrane helps prevent surface particulates such as fibers and dust from becoming airborne by binding them together and locking them down to the surface. Airborne particulates will adhere to Grip-Tack's soft tacky finish to help minimize environmental contamination during demolition and component removal projects. Grip-Tack should be spray applied at a rate of 100 - 200 sq.ft. per gallon.

LOCKDOWN: Sealing microscopic residual fibers after asbestos removal is mandatory on every project. Prior to post-removal air monitoring, apply one coat to all exposed surfaces.

PULLDOWN BY MISTING: Pulldown by misting the contaminated air is an effective control technique prior to post-removal air monitoring. To pull down contaminants

Properties

Product Specifications

Solids by Weight \pm 2%:	50.0%
Solids by Volume \pm 2%:	50.0%
Viscosity at 70°F:	50-60 Krebs units
Specular Gloss:	90° \pm 5 @ 60°
Flash Point:	Non-combustible
Shelf Life:	12 Months Min. (Original Sealed Container)
Calculated VOC:	0 grams/liter

Coverage

Smooth Surfaces:	200 ft ² /gal
Porous Surfaces:	100-200 ft ² /gal

Drying Times (@ 70 - 77°F, 50% R.H.)

To Touch:	1 hour
To Recoat:	1 hour
Minimum Application Temp:	50°F (10°C)

Available Package Sizes

5 gallon containers	
Weight Per Gallon \pm .5lbs:	8.35 lbs/gal



Application Information

such as dust and free-floating asbestos fibers effectively, stand in the center of the room and hold the spray gun as close to the ceiling as possible. A mist should then be sprayed parallel to surfaces in every direction or in a circle. In containment, apply one coat to the polyethylene walls and floor.

APPLICATION TOOLS

SPRAY

Pressure: 1900 - 2500 P.S.I.

Tip: .015 - .019

COVERAGE

Smooth Surfaces: 200 sq. ft.

Porous Surfaces: 100-200 sq. ft.

DRYING TIME @ 70°F 50% R.H

To Touch - 1 hour

To Recoat - 1 hour

CLEANUP

Clean tools and drippings with warm soapy water before coating dries. Follow equipment manufacturer's directions to clean spray equipment. Dispose of all waste according to current local, state and federal regulations.

PRECAUTIONS

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F (32°C). Stir thoroughly. Do not add solvents, oils, or colors in oil or mix with other coatings. Do not apply when air or surface temperature is below 60°F or when drying conditions are poor. Use adequate ventilation.

CAUTION!

KEEP OUT OF REACH OF CHILDREN.

Do not take internally. Close container after each use.

Keep from freezing

Store between 40°F (4.5°C) and 90°F (32°C)

24 hour Emergency "CHEM-TEL" - 800.255.3924

For Technical Information call 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Construction, Inc., nor its agents shall be responsible for the use or results of use of this product or any injury, loss or damage, direct or consequential. We recommend that the prospective user determine the suitability of this product for each specific project and for the health and safety of personnel working in the area.

Grip-Tack, the Grip-Tack Logo and other marks in this literature are trademarks of ICP Construction, Inc.