


Scan this QR code with your smartphone for:

- Product Data Sheet and SDS
- Additional Product Information



Professional Products  
Professional Results

24 HOUR EMERGENCY CHEMTEL - 1-800-255-3924

IAQ 6200EZ is a white, tintable mold resistant coating for professional use, that contains a fungistatic agent to resist mold growth on the dry coating surface. IAQ 6200EZ is value engineered with high volum projects in mind. IAQ 6200EZ is a flexible and permeable 100% acrylic water based coating. IAQ 6200EZ has successfully passed both ASTM G-21 and ASTM D-3273 mold resistance testing with the highest possible ratings. IAQ 6200EZ is recommended for use on wood, plaster, wallboard, sheetrock, concrete, masonry block, primed metal and galvanized metal. IAQ 6200EZ can also be used on new structural materials during building construction.

#### SURFACE PREPARATION

Surfaces to be coated must be free of dust, mildew, mold, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap and other surface contamination. Clean mold stained surfaces with IAQ Advanced Peroxide Cleaner, or use an EPA registered antimicrobial disinfectant cleaner such as IAQ 2000, IAQ 2500, ShockWave or ShockWave RTU.

Patch irregularities with vinyl patching paste or an appropriate patching compound. IAQ 6200EZ is self-priming over bare sheetrock, composition board, ceiling tile and concrete.

WALLBOARD, SHEETROCK, GYPSUM BOARD - Joint cement should be sanded smooth, but avoid abrading the paper.

FERROUS METAL - Clean, then prime with suitable rust inhibiting direct-to-metal primer.

WOOD - Seal knots and stains with stain-blocking primer.

MASONRY BLOCK - Apply one coat of block filler if a denser surface is desired.

#### APPLICATION TOOLS

**Airless sprayer:** Primary & Recommended Method

- Tip: 0.013"-0.019"
- Pressure: 1800-2400 psi

**Roller:** for small or confined areas.

- ½" nap synthetic roller

**Brush:** will require 2 coats.

- Synthetic, nylon, polyester

#### TINTING

IAQ 6200EZ may be tinted to any off-white or pastel based color. Add up to 2 oz. of universal colorant per gallon. Start with 50% of the tinting formula and adjust as necessary.

#### PRODUCT APPLICATION

Apply IAQ 6200EZ generously and uniformly by airless spray (preferred), or brush or roller. Apply one coat of IAQ 6200EZ and ensure that the finished surface is properly sealed. To ensure that the finished surface is properly sealed, two-coats may be required on some porous surfaces.

#### COVERAGE

Smooth Surfaces: 300-400 ft<sup>2</sup>/gal.

Porous Surfaces: 150-300 ft<sup>2</sup>/gal.

#### DRYING TIME @ 70°F 50% R.H

To Touch: 1 Hour

Recoat: 4 Hours

#### CLEANUP

Clean tools and drippings with warm soapy water before 6200EZ dries. Dispose of waste according to all existing local, state and federal regulations.

#### PRECAUTIONS

Store in a dry place at temperatures between 40°F (4.5°C) and 90°F. (32°C). Stir thoroughly. Do not mix with any other coatings, solvents or colors in oil. The IAQ 6200EZ coating is resistant to mold only on the surface of the coating. No mold resistance claim is made other than to the coating itself. The use of this product does not protect users or others against food-borne or disease-causing bacteria, viruses, germs or other disease-causing organisms. Do not apply when air or surface temperature is below 50°F, or when drying conditions are poor or when surfaces are above a 15% moisture level content, or 95°F. Use adequate ventilation during application. When applying with a sprayer, wear a NIOSH approved respirator with any R, P, N or HE filter. For interior use only.

**WARNING!** Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Hazardous dust may be formed when sanded. Do not breathe dust. Use adequate ventilation.

#### VOC CONTENT

<1 g/L

MADE IN USA WITH GLOBALLY SOURCED MATERIALS

# IAQ 6200EZ

MOLD  
RESISTANT  
COATING

VALUE LEADER FORMULATED FOR  
LARGE JOBS & NEW CONSTRUCTION

FOR LASTING MOLD RESISTANCE  
ON THE DRY COATING FILM

TINTABLE (2oz per gallon/max of colorant)

NET CONTENTS:  
5 GALLONS (18.93L)

FOR FAST  
& EZ MOLD  
RESISTANCE\*

\*Resists mold growth on  
the dry coating surface

WHITE  
INTERIOR ONLY

#### PRECAUTIONS

Do not handle until all safety precautions have been read and understood. **KEEP OUT OF REACH OF CHILDREN. FIRST AID:** If exposed or concerned, get medical advice/attention. **Contents:** Titanium dioxide, zinc oxide. **STORAGE:** Store locked up. **DISPOSAL:** Dispose of contents/container to an approved waste disposal plant. Keep from freezing. Store between 40-90F (4.5-32C).

#### FOR TECHNICAL INFORMATION CALL 800.342.3755

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither ICP Building Solutions Group, nor its agents shall be responsible for the use of this product or any procedures or apparatus mentioned. We recommend that the prospective user determine the suitability for each specific project and for the health and safety of personnel working in the area.

For additional information check Safety Data Sheet (SDS) or Product Data Sheet (PDS) available online at [www.fiberlock.com](http://www.fiberlock.com).

**WARNING! If you scrape, sand or remove old paint it may generate dust containing lead or titanium dioxide. Avoid inhaling dust. Wear a NIOSH-approved respirator to control exposure. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMENT SHOULD ALSO AVOID EXPOSURE. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1.800.424.LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead)**

IAQ, the IAQ Logo and other marks on this label are trademarks of ICP Building Solutions Group.



WARNING: This product can expose you to chemicals including titanium dioxide (airborne, unbound particles of respirable size) a chemical known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

8364-5  
White



150 Dascomb Rd.  
Andover, MA 01810  
(800) 342-3755  
[www.fiberlock.com](http://www.fiberlock.com)  
Rev. 12.15.25

